



Test Report: HLG-320H-42

320W Single Output Switching Power Supply

■ DESIGN VERIFY TEST

Output Function Test

Input Function Test

Protection Function Test

Component Stress Test

■ SAFETY & E.M.C. TEST

Safety Test

E.M.C. Test

■ RELIABILITY TEST

ENVIRONMENT TEST

DESIGN VERIFY TEST

OUTPUT FUNCTION TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT
1	RIPPLE & NOISE	V1 : 250 mVp-p (Max)	I/P : 230VAC O/P : FULL LOAD Ta : 25°C	V1 : 22.8 mVp-p (Max)
2	CONSTANT CURRENT REGION	21V ~42V	I/P: 230 VAC O/P:CV MODE Ta:25°C	O/P=21V : 7.66A O/P=41V: 7.65 A
3	OUTPUT VOLTAGE ADJUST RANGE	CH1 : 38 V ~ 45 V	I/P : 230 VAC I/P : 115 VAC O/P : MIN LOAD Ta : 25°C	36.91 V~ 45.95 V/ 230 VAC 36.91 V ~ 45.95 V/ 115 VAC
4	OUTPUT CURRENT ADJUST RANGE	CH1 : 3.8A ~ 7.65A	I/P : 230 VAC I/P : 115 VAC O/P : FULL LOAD Ta : 25°C	3.463 A~ 8.591 A/ 230 VAC 3.464 A~ 8.599 A/ 115 VAC
5	OUTPUT VOLTAGE TOLERANCE	V1 : 1 %~ -1 % (Max)	I/P : 100 VAC / 305 VAC O/P : FULL/ MIN LOAD Ta : 25°C	V1 : 0.09 %~ -0.09 %
6	LINE REGULATION	V1 : 0.5 %~ -0.5 % (Max)	I/P : 100 VAC ~ 305 VAC O/P : FULL LOAD Ta : 25°C	V1 : 0 %~ 0 %
7	LOAD REGULATION	V1 : 0.5 %~ -0.5 % (Max)	I/P : 230 VAC O/P : FULL ~MIN LOAD Ta : 25°C	V1 : 0.08 %~ -0.08 %
8	SET UP TIME	230VAC : 500 ms (Max) 115VAC : 2500 ms(Max)	I/P : 230 VAC I/P : 115 VAC O/P : FULL LOAD Ta : 25°C	230VAC/ 384 ms 115VAC/ 780 ms
9	RISE TIME	230VAC : 80 ms (Max) 115VAC : 80 ms (Max)	I/P : 230 VAC I/P : 115 VAC O/P : FULL LOAD Ta : 25°C	230VAC/ 33 ms 115VAC/ 36 ms
10	HOLD UP TIME	230VAC : 15 ms (TYP) 115VAC : 15 ms (TYP)	I/P : 230 VAC I/P : 115 VAC O/P : FULL LOAD Ta : 25°C	230VAC/ 25 ms 115VAC/ 82 ms
11	OVER/UNDERSHOOT TEST	< ±5%	I/P : 230 VAC O/P : FULL LOAD Ta : 25°C	TEST : <5 %

12	DYNAMIC LOAD	V1 : 4200 mVp-p	I/P : 230 VAC (1).O/P : FULL /Min LOAD 90%DUTY/ 1KHZ (2).O/P : FULL /Min LOAD 50%DUTY/ 120HZ Ta : 25℃				(1)280 mVp-p (2)1056 mVp-p																																																																																																																																																																												
13	DIMMER TEST (B Type only)	SPEC: * IP67 rated. Output constant current level can be adjusted through output cable by connecting a resistor or 1 ~ 10Vdc or 10V PWM signal between DIM+ and DIM- *Reference resistance value for output current adjustment (Typical) <table><tr><td>Resistance value</td><td>10K</td><td>20K</td><td>30K</td><td>40K</td><td>50K</td><td>60K</td><td>70K</td><td>80K</td><td>90K</td><td>100K</td></tr><tr><td>Output current</td><td>10%</td><td>20%</td><td>30%</td><td>40%</td><td>50%</td><td>60%</td><td>70%</td><td>80%</td><td>90%</td><td>100%</td></tr></table> *1 ~ 10V dimming function for output current adjustment (Typical) <table><tr><td>Dimming value</td><td>1V</td><td>2V</td><td>3V</td><td>4V</td><td>5V</td><td>6V</td><td>7V</td><td>8V</td><td>9V</td><td>10V</td></tr><tr><td>Output current</td><td>10%</td><td>20%</td><td>30%</td><td>40%</td><td>50%</td><td>60%</td><td>70%</td><td>80%</td><td>90%</td><td>100%</td></tr></table> *10V PWM signal for output current adjustment (Typical) <table><tr><td>Duty value</td><td>10%</td><td>20%</td><td>30%</td><td>40%</td><td>50%</td><td>60%</td><td>70%</td><td>80%</td><td>90%</td><td>100%</td></tr><tr><td>Output current</td><td>10%</td><td>20%</td><td>30%</td><td>40%</td><td>50%</td><td>60%</td><td>70%</td><td>80%</td><td>90%</td><td>100%</td></tr></table> TEST RESULT: I/P : 230 VAC ;Ta : 25℃ <table><tr><td rowspan="3">1</td><td>Resistance value</td><td>10K</td><td>20K</td><td>30K</td><td>40K</td><td>50K</td><td>60K</td><td>70K</td><td>80K</td><td>90K</td><td>100K</td></tr><tr><td>Output current</td><td>0.817A</td><td>1.545A</td><td>2.289A</td><td>3.025A</td><td>3.755A</td><td>4.513A</td><td>5.197A</td><td>5.978A</td><td>6.723A</td><td>7.449A</td></tr><tr><td>%</td><td>10.68%</td><td>20.20%</td><td>29.92%</td><td>39.54%</td><td>49.08%</td><td>58.99%</td><td>67.93%</td><td>78.14%</td><td>87.88%</td><td>97.37%</td></tr><tr><td rowspan="3">2</td><td>Dimming value</td><td>1V</td><td>2V</td><td>3V</td><td>4V</td><td>5V</td><td>6V</td><td>7V</td><td>8V</td><td>9V</td><td>10V</td></tr><tr><td>Output current</td><td>0.852A</td><td>1.620A</td><td>2.395A</td><td>3.165A</td><td>3.932A</td><td>4.687A</td><td>5.465A</td><td>6.211A</td><td>6.985A</td><td>7.661A</td></tr><tr><td>%</td><td>11.14%</td><td>21.18%</td><td>31.31%</td><td>41.37%</td><td>51.40%</td><td>61.27%</td><td>71.44%</td><td>81.19%</td><td>91.31%</td><td>100.14%</td></tr><tr><td rowspan="3">3</td><td>Duty value</td><td>10%</td><td>20%</td><td>30%</td><td>40%</td><td>50%</td><td>60%</td><td>70%</td><td>80%</td><td>90%</td><td>100%</td></tr><tr><td>Output current</td><td>0.886A</td><td>1.650A</td><td>2.407A</td><td>3.163A</td><td>3.919A</td><td>4.674A</td><td>5.427A</td><td>6.180A</td><td>6.931A</td><td>7.675A</td></tr><tr><td>%</td><td>11.58%</td><td>21.57%</td><td>31.46%</td><td>41.35%</td><td>51.23%</td><td>61.10%</td><td>70.94%</td><td>80.78%</td><td>90.60%</td><td>100.33%</td></tr></table>										Resistance value	10K	20K	30K	40K	50K	60K	70K	80K	90K	100K	Output current	10%	20%	30%	40%	50%	60%	70%	80%	90%	100%	Dimming value	1V	2V	3V	4V	5V	6V	7V	8V	9V	10V	Output current	10%	20%	30%	40%	50%	60%	70%	80%	90%	100%	Duty value	10%	20%	30%	40%	50%	60%	70%	80%	90%	100%	Output current	10%	20%	30%	40%	50%	60%	70%	80%	90%	100%	1	Resistance value	10K	20K	30K	40K	50K	60K	70K	80K	90K	100K	Output current	0.817A	1.545A	2.289A	3.025A	3.755A	4.513A	5.197A	5.978A	6.723A	7.449A	%	10.68%	20.20%	29.92%	39.54%	49.08%	58.99%	67.93%	78.14%	87.88%	97.37%	2	Dimming value	1V	2V	3V	4V	5V	6V	7V	8V	9V	10V	Output current	0.852A	1.620A	2.395A	3.165A	3.932A	4.687A	5.465A	6.211A	6.985A	7.661A	%	11.14%	21.18%	31.31%	41.37%	51.40%	61.27%	71.44%	81.19%	91.31%	100.14%	3	Duty value	10%	20%	30%	40%	50%	60%	70%	80%	90%	100%	Output current	0.886A	1.650A	2.407A	3.163A	3.919A	4.674A	5.427A	6.180A	6.931A	7.675A	%	11.58%	21.57%	31.46%	41.35%	51.23%	61.10%	70.94%	80.78%	90.60%	100.33%
Resistance value	10K	20K	30K	40K	50K	60K	70K	80K	90K	100K																																																																																																																																																																									
Output current	10%	20%	30%	40%	50%	60%	70%	80%	90%	100%																																																																																																																																																																									
Dimming value	1V	2V	3V	4V	5V	6V	7V	8V	9V	10V																																																																																																																																																																									
Output current	10%	20%	30%	40%	50%	60%	70%	80%	90%	100%																																																																																																																																																																									
Duty value	10%	20%	30%	40%	50%	60%	70%	80%	90%	100%																																																																																																																																																																									
Output current	10%	20%	30%	40%	50%	60%	70%	80%	90%	100%																																																																																																																																																																									
1	Resistance value	10K	20K	30K	40K	50K	60K	70K	80K	90K	100K																																																																																																																																																																								
	Output current	0.817A	1.545A	2.289A	3.025A	3.755A	4.513A	5.197A	5.978A	6.723A	7.449A																																																																																																																																																																								
	%	10.68%	20.20%	29.92%	39.54%	49.08%	58.99%	67.93%	78.14%	87.88%	97.37%																																																																																																																																																																								
2	Dimming value	1V	2V	3V	4V	5V	6V	7V	8V	9V	10V																																																																																																																																																																								
	Output current	0.852A	1.620A	2.395A	3.165A	3.932A	4.687A	5.465A	6.211A	6.985A	7.661A																																																																																																																																																																								
	%	11.14%	21.18%	31.31%	41.37%	51.40%	61.27%	71.44%	81.19%	91.31%	100.14%																																																																																																																																																																								
3	Duty value	10%	20%	30%	40%	50%	60%	70%	80%	90%	100%																																																																																																																																																																								
	Output current	0.886A	1.650A	2.407A	3.163A	3.919A	4.674A	5.427A	6.180A	6.931A	7.675A																																																																																																																																																																								
	%	11.58%	21.57%	31.46%	41.35%	51.23%	61.10%	70.94%	80.78%	90.60%	100.33%																																																																																																																																																																								

INPUT FUNCTION TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT
1	INPUT VOLTAGE RANGE	90VAC~305 VAC	I/P : TESTING O/P : FULL LOAD Ta : 25°C	60 V~305V
			I/P : LOW-LINE-3V= 87 V HIGH-LINE+10V=315V O/P : FULL/MIN LOAD ON : 30 Sec . OFF : 30 Sec 10MIN (AC POWER ON/OFF NO DAMAGE)	TEST : OK
2	INPUT FREQUENCY RANGE	47HZ ~63 HZ NO DAMAGE	I/P : 100VAC ~ 305 VAC O/P : FULL~MIN LOAD Ta : 25°C	TEST : OK
3	POWER FACTOR	0.95/ 230 VAC FULL LOAD (TYP) 0.98/ 115 VAC FULL LOAD (TYP) 0.94/ 277 VAC FULL LOAD (TYP)	I/P : 230 VAC I/P : 115 VAC I/P : 277 VAC O/P : FULL LOAD Ta : 25°C	PF=0.975 /230V/100%LOAD PF=0.998 /115V/100%LOAD PF=0.95 / 277V/100%LOAD
4	EFFICIENCY	95 % (TYP) 95 % (TYP)	I/P : 230 VAC I/P : 277 VAC O/P : FULL LOAD Ta : 25°C	95.215 % 95.704 %
5	INPUT CURRENT	277V/ 1.45 A (TYP) 230V/ 1.65 A (TYP) 115V/ 3.5 A (TYP)	I/P : 277 VAC I/P : 230 VAC I/P : 115 VAC O/P : FULL LOAD Ta : 25°C	I = 1.2764 A/ 277VAC I = 1.5016 A/ 230 VAC I = 3.109 A/ 115 VAC
6	INRUSH CURRENT	230V/ 70 A (TYP)	I/P : 230 VAC O/P : FULL LOAD Ta : 25°C	I = 58 A/ 230 VAC
7	LEAKAGE CURRENT	< 0.75 mA / 277VAC	I/P : 305 VAC O/P : Min LOAD Ta : 25°C	L-FG : 0.2 mA N-FG : 0.2 mA
8	TOTAL HARMONIC DISTORTION	THD< 20% when output loading ≥ 50% at 115VAC/230VAC input and output loading ≥ 75% at 277VAC input	I/P : 115 VAC I/P : 230 VAC O/P : 50% LOAD I/P : 277 VAC O/P : 75%LOAD Ta : 25°C	THD : 5.5 /115VAC THD : 10.8 /230VAC THD : 11.4 /277VAC

PROTECTION FUNCTION TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT
1	OVER LOAD PROTECTION	95 % ~ 108 %	I/P : 230 VAC I/P : 115 VAC O/P : TESTING Ta : 25°C	105.39 %/ 230 VAC 105.37 %/ 115 VAC Constant current limiting, recovers automatically after fault condition is removed
2	OVER VOLTAGE PROTECTION	CH1 : 46.5V ~ 53 V	I/P : 230 VAC I/P : 115 VAC O/P : MIN LOAD Ta : 25°C	47.795 V/ 230 VAC 47.941V/ 115 VAC Shut down and latch off o/p voltage, re-power on to recover
3	OVER TEMPERATURE PROTECTION	NO DAMAGE	I/P : 230 VAC O/P : FULL LOAD	O.T.P. Active Shut down and latch off o/p voltage, re-power on to recover
4	SHORT PROTECTION	SHORT EVERY OUTPUT 1 HOUR NO DAMAGE	I/P : 305 VAC O/P : FULL LOAD Ta : 25°C	NO DAMAGE Hiccup Mode

COMPONENT STRESS TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT
1	Power Transistor (D to S) or (C to E) Peak Voltage	Q5 Rated : 20A/600V	I/P : High-Line +3V = 308 V O/P : (1)Full Load Turn on (2) Output Short (3)Full load continue Ta : 25℃	(1) 476 V (2) 492 V (3) 466 V
2	Diode Peak Voltage	Q101 Rated : 66A/120V Q102 Rated : 66A/120V	I/P : High-Line +3V = 308 V O/P : (1)Full Load Turn on (2)Output Short (3)Full load continue Ta : 25℃	(1) 98 V (2) 30.8 V (3) 96.4 V (1) 102 V (2) 98 V (3) 99.2 V
3	Input Capacitor Voltage	C5 Rated : 220u/450V	I/P : High-Line +3V = 308 V O/P : (1)Full Load Turn on /Off (2) Min load Turn on /Off (3)Full Load /Min load Change Ta : 25℃	(1) 427.61 V (2) 438.58 V (3) 436.98 V
4	Control IC Voltage Test	U900 Rated : 8.85V~16V	I/P : High-Line +3V = 308 V O/P : (1)Full Load Turn on /Off (2) Min load Turn on /Off (3)Full Load /Min load Change Ta : 25℃	(1) 13.567 V (2) 13.544 V (3) 13.573 V
5	P.F.C Transistor (D to S) or (C to E) Peak Voltage	Q 1 Rated : 20A/600V	I/P : High-Line +3V = 308 V O/P : (1)Full Load Turn on (2) Output Short (3)Full load continue Ta : 25℃	(1) 584 V (2) 496 V (3) 568 V

SAFETY & E.M.C. TEST

SAFETY TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT
1	WITHSTAND VOLTAGE	I/P-O/P : 3.75KVAC/min I/P-FG : 2KVAC/min<4.5mA O/P-FG : 1.5 KVAC/min	I/P-O/P : 4 KVAC/min I/P-FG : 2.4 KVAC/min O/P-FG : 1.8 KVAC/min Ta : 25°C	I/P-O/P : 2.485 mA I/P-FG : 1.999 mA O/P-FG : 1.572 mA NO DAMAGE
2	ISOLATION RESISTANCE	I/P-O/P : 500VDC>100MΩ I/P-FG : 500VDC>100MΩ O/P-FG : 500VDC>100MΩ	I/P-O/P : 500 VDC I/P-FG : 500 VDC O/P-FG : 500 VDC Ta : 25°C /70%RH	I/P-O/P : 30 GΩ I/P-FG : 30 GΩ O/P-FG : 30 GΩ NO DAMAGE
3	GROUNDING CONTINUITY	FG(PE) TO CHASSIS OR TRACE < 100 mΩ	40 A / 2min Ta : 25°C / 70%RH	20 mΩ

E.M.C TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT
1	HARMONIC	EN61000-3-2 CLASS A CLASS C	I/P:230 VAC / 50HZ O/P:100%ELECTRONIC LOAD O/P:100% LED LOAD Ta:25°C	PASS
2	CONDUCTION	EN55022; EN55015 CLASS B	I/P : 230 VAC (50HZ) O/P : FULL/50% LOAD Ta : 25°C	PASS Test by certified Lab
3	RADIATION	EN55022 ;EN55015 CLASS B	I/P : 230 VAC (50HZ) O/P : FULL LOAD Ta : 25°C	PASS Test by certified Lab
4	E.S.D	EN61000-4-2 INDUSTRY AIR : 8KV / Contact : 4KV	I/P : 230 VAC/50HZ O/P : FULL LOAD Ta : 25°C	CRITERIA A
5	E.F.T	EN61000-4-4 INDUSTRY INPUT : 2KV	I/P : 230 VAC/50HZ O/P : FULL LOAD Ta : 25°C	CRITERIA A
6	SURGE	IEC61000-4-5 INDUSTRY L-N : 2KV L,N-PE : 4KV	I/P : 230 VAC/50HZ O/P : FULL LOAD Ta : 25°C	CRITERIA A
7	Test by certified Lab & Test Report Prepare. Any contradictions of the test results, please refer to the latest EMC test report.			

RELIABILITY TEST

ENVIRONMENT TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT																																																																																																
1	TEMPERATURE RISE TEST	MODEL : HLG-320H-24 1. ROOM AMBIENT BURN-IN : 13 HRS I/P : 230VAC O/P : FULL LOAD Ta=30.6 °C 2. HIGH AMBIENT BURN-IN : 16.5 HRS I/P : 230VAC O/P : FULL LOAD Ta=67.8 °C <table><thead><tr><th>NO</th><th>Position</th><th>ROOM AMBIENT Ta= 30.6 °C</th><th>HIGH AMBIENT Ta=67.8 °C</th></tr></thead><tbody><tr><td>1</td><td>LF1</td><td>60.3°C</td><td>91.5°C</td></tr><tr><td>2</td><td>L2</td><td>64.9°C</td><td>95.7°C</td></tr><tr><td>3</td><td>C11</td><td>66.8°C</td><td>97.7°C</td></tr><tr><td>4</td><td>BD1</td><td>67.0°C</td><td>97.9°C</td></tr><tr><td>5</td><td>Q1</td><td>66.7°C</td><td>97.3°C</td></tr><tr><td>6</td><td>C5</td><td>66.1°C</td><td>96.5°C</td></tr><tr><td>7</td><td>L1</td><td>68.5°C</td><td>98.5°C</td></tr><tr><td>8</td><td>D2</td><td>67.7°C</td><td>98.5°C</td></tr><tr><td>9</td><td>C13</td><td>65.9°C</td><td>96.7°C</td></tr><tr><td>10</td><td>C902</td><td>65.5°C</td><td>96.4°C</td></tr><tr><td>11</td><td>C40</td><td>67.0°C</td><td>97.6°C</td></tr><tr><td>12</td><td>D3</td><td>70.7°C</td><td>100.9°C</td></tr><tr><td>13</td><td>D41</td><td>65.4°C</td><td>95.8°C</td></tr><tr><td>14</td><td>C906</td><td>63.6°C</td><td>94.7°C</td></tr><tr><td>15</td><td>C205</td><td>64.7°C</td><td>96.2°C</td></tr><tr><td>16</td><td>T1</td><td>68.8°C</td><td>100.7°C</td></tr><tr><td>17</td><td>C102</td><td>62.3°C</td><td>94.1°C</td></tr><tr><td>18</td><td>C106</td><td>62.6°C</td><td>94.5°C</td></tr><tr><td>19</td><td>Q101</td><td>65.2°C</td><td>96.5°C</td></tr><tr><td>20</td><td>C104</td><td>61.6°C</td><td>93.2°C</td></tr><tr><td>21</td><td>U900</td><td>62.7°C</td><td>93.8°C</td></tr><tr><td>22</td><td>RTH2</td><td>62.4°C</td><td>93.8°C</td></tr><tr><td>23</td><td>LF100</td><td>62.5°C</td><td>94.8°C</td></tr></tbody></table>			NO	Position	ROOM AMBIENT Ta= 30.6 °C	HIGH AMBIENT Ta=67.8 °C	1	LF1	60.3°C	91.5°C	2	L2	64.9°C	95.7°C	3	C11	66.8°C	97.7°C	4	BD1	67.0°C	97.9°C	5	Q1	66.7°C	97.3°C	6	C5	66.1°C	96.5°C	7	L1	68.5°C	98.5°C	8	D2	67.7°C	98.5°C	9	C13	65.9°C	96.7°C	10	C902	65.5°C	96.4°C	11	C40	67.0°C	97.6°C	12	D3	70.7°C	100.9°C	13	D41	65.4°C	95.8°C	14	C906	63.6°C	94.7°C	15	C205	64.7°C	96.2°C	16	T1	68.8°C	100.7°C	17	C102	62.3°C	94.1°C	18	C106	62.6°C	94.5°C	19	Q101	65.2°C	96.5°C	20	C104	61.6°C	93.2°C	21	U900	62.7°C	93.8°C	22	RTH2	62.4°C	93.8°C	23	LF100	62.5°C	94.8°C
NO	Position	ROOM AMBIENT Ta= 30.6 °C	HIGH AMBIENT Ta=67.8 °C																																																																																																	
1	LF1	60.3°C	91.5°C																																																																																																	
2	L2	64.9°C	95.7°C																																																																																																	
3	C11	66.8°C	97.7°C																																																																																																	
4	BD1	67.0°C	97.9°C																																																																																																	
5	Q1	66.7°C	97.3°C																																																																																																	
6	C5	66.1°C	96.5°C																																																																																																	
7	L1	68.5°C	98.5°C																																																																																																	
8	D2	67.7°C	98.5°C																																																																																																	
9	C13	65.9°C	96.7°C																																																																																																	
10	C902	65.5°C	96.4°C																																																																																																	
11	C40	67.0°C	97.6°C																																																																																																	
12	D3	70.7°C	100.9°C																																																																																																	
13	D41	65.4°C	95.8°C																																																																																																	
14	C906	63.6°C	94.7°C																																																																																																	
15	C205	64.7°C	96.2°C																																																																																																	
16	T1	68.8°C	100.7°C																																																																																																	
17	C102	62.3°C	94.1°C																																																																																																	
18	C106	62.6°C	94.5°C																																																																																																	
19	Q101	65.2°C	96.5°C																																																																																																	
20	C104	61.6°C	93.2°C																																																																																																	
21	U900	62.7°C	93.8°C																																																																																																	
22	RTH2	62.4°C	93.8°C																																																																																																	
23	LF100	62.5°C	94.8°C																																																																																																	
2	LOW TEMPERATURE TURN ON TEST	TURN ON AFTER 2 HOUR	I/P : 305VAC/100VAC O/P : 100 % LOAD Ta= -40 °C	TEST : OK																																																																																																
3	HIGH HUMIDITY HIGH TEMPERATURE HIGH VOLTAGE TURN ON TEST	AFTER 12 HOURS IN CHAMBER ON CONTROL 60 °C NO DAMAGE	I/P : 305 VAC O/P : FULL LOAD Ta= 60 °C HUMIDITY= 95 %R.H	TEST : OK																																																																																																
4	TEMPERATURE COEFFICIENT	±0.03 %(0~50°C)	I/P : 230 VAC O/P : FULL LOAD	± 0.003 %(0~50°C)																																																																																																
5	STORAGE TEMPERATURE TEST	1. Thermal shock Temperature : -45°C~ +90°C 2. Temperature change rate : 25°C / MIN 3. Dwell time low and high temperature : 30 MIN/EACH 4. Total test cycle : 5 CYCLE 5. Input/Output condition : STATIC		OK																																																																																																

6	THERMAL SHOCK TEST	1. Thermal shock Temperature : -45°C ~ +65°C 2. Temperature change rate : 25°C / MIN 3. Dwell time low and high temperature : 30 MIN/EACH 4. Total test cycle : 10 CYCLE 5. Input/Output condition : 230VAC/Full Load AC ON/OFF TEST turn on 58sec ; turn off 2sec	OK
7	VIBRATION TEST	1 Carton & 1 Set (1) Waveform : Sine Wave (2) Frequency : 10~500Hz (3) Sweep Time : 12min/sweep cycle (4) Acceleration : 5G (5) Test Time : 72min in each axis (X.Y.Z) (6) Ta : 25°C	TEST : OK
8	CAPACITOR LIFE CYCLE	HLG-320H-24:SUPPOSE C106 IS THE MOST CRITICAL COMPONENT (1) I/P : 230VAC O/P : FULL LOAD Tc= 75 °C LIFE TIME (2) I/P : 230VAC O/P : 75% LOAD Tc= 75 °C LIFE TIME (3) I/P : 230VAC O/P : 50% LOAD Tc= 75 °C LIFE TIME	(1) 78859HRS (2) 89035HRS (3) 95653HRS
9	MTBF	Conducted by Parts Stress Analysis Prediction 157.1K hrs min. MIL-HDBK-217F (25°C)	
10	Ongoing Reliability Test	I/P : 230VAC O/P : FULL LOAD TA=50°C Demonstration Mean Time Between Failure : 62,000 hours	

TEST RESULT	TESTER	REVIEW	APPROVAL
PASS	DANIEL GAO	SANFORD SU	VINCENT TSENG

2009/08/04 A50-F023

