



Test Report: ELP-75-24

75W Single Output with PFC Function

■ DESIGN VERIFY TEST

Output Function Test

Input Function Test

Protection Function Test

Component Stress Test

■ SAFETY & E.M.C. TEST

Safety Test

E.M.C. Test

■ RELIABILITY TEST

ENVIRONMENT TEST

DESIGN VERIFY TEST

OUTPUT FUNCTION TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	RIPPLE & NOISE	V1 : 240 mVp-p (Max)	I/P : 230VAC O/P : FULL LOAD Ta : 25°C	V1 : 75 mVp-p (Max)	P
2	OUTPUT VOLTAGE ADJUST RANGE	CH1 : 21.6 V ~26.4 V	I/P : 230 VAC I/P : 115 VAC O/P : MIN LOAD Ta : 25°C	21.16 V ~ 27.35 V/ 230 VAC 21.16 V ~ 27.35 V/ 115 VAC	P
3	OUTPUT VOLTAGE TOLERANCE	V1 : 1 %~ -1 % (Max)	I/P : 100 VAC / 264 VAC O/P : FULL/ MIN LOAD Ta : 25°C	V1 : 0.05 %~ -0.05 %	P
4	LINE REGULATION	V1 : 0.5 %~ -0.5 % (Max)	I/P : 100 VAC ~ 264 VAC O/P : FULL LOAD Ta : 25°C	V1 : 0 %~ 0 %	P
5	LOAD REGULATION	V1 : 1 %~ -1 % (Max)	I/P : 230 VAC O/P : FULL ~MIN LOAD Ta : 25°C	V1 : 0.05 %~ -0.05 %	P
6	SET UP TIME	230VAC : 2500 ms (Max) 115VAC : 2500 ms(Max)	I/P : 230 VAC I/P : 115 VAC O/P : FULL LOAD Ta : 25°C	230VAC/ 749 ms 115VAC/ 1498 ms	P
7	RISE TIME	230VAC : 50 ms (Max) 115VAC : 50 ms (Max)	I/P : 230 VAC I/P : 115 VAC O/P : FULL LOAD Ta : 25°C	230VAC/ 26 ms 115VAC/ 18 ms	P
8	HOLD UP TIME	230VAC : 20 ms (TYP) 115VAC : 20 ms (TYP)	I/P : 230 VAC I/P : 115 VAC O/P : FULL LOAD Ta : 25°C	230VAC/ 93 ms 115VAC/ 86 ms	P
9	OVER/UNDERSHOOT TEST	< ±5%	I/P : 230 VAC O/P : FULL LOAD Ta : 25°C	TEST : < 5 %	P
10	DYNAMIC LOAD	V1 : 2400 mVp-p	I/P : 230 VAC O/P : FULL /Min LOAD 90%DUTY/ 1KHZ Ta : 25°C	165 mVp-p	P

INPUT FUNCTION TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	INPUT VOLTAGE RANGE	90VAC~264 VAC	I/P : TESTING O/P : FULL LOAD Ta : 25°C I/P : LOW-LINE-3V= 87 V HIGH-LINE+15%=300 V O/P : FULL/MIN LOAD ON : 30 Sec . OFF : 30 Sec 10MIN (AC POWER ON/OFF NO DAMAGE)	78 V~264V TEST : OK	P
2	INPUT FREQUENCY RANGE	47HZ ~63 HZ NO DAMAGE OSC	I/P : 100 VAC ~ 264 VAC O/P : FULL~MIN LOAD Ta : 25°C	TEST : OK	P
3	POWER FACTOR	0.95 / 230 VAC(TYP) 0.98 / 115 VAC(TYP)	I/P : 230 VAC I/P : 115 VAC O/P : FULL LOAD Ta : 25°C	PF= 0.96 / 230 VAC PF= 1 / 115 VAC	P
4	EFFICIENCY	90% (TYP)	I/P : 230 VAC O/P : FULL LOAD Ta : 25°C	90.89 %	P
5	INPUT CURRENT	230V/ 1 A (TYP) 115V/ 1.8 A (TYP)	I/P : 230 VAC I/P : 115 VAC O/P : FULL LOAD Ta : 25°C	I = 0.37 A/ 230 VAC I = 0.74 A/ 115 VAC	P
6	INRUSH CURRENT	230V/ 60 A (TYP) COLD START	I/P : 230 VAC I O/P : FULL LOAD Ta : 25°C	I = 36 A/ 230 VAC	P
7	LEAKAGE CURRENT	< 1 mA / 240 VAC	I/P : 264 VAC O/P : Min LOAD Ta : 25°C	L-FG : 0.46 mA N-FG : 0.44 mA	P
8	NO LOAD CONSUMPTION	< 0.5W /230V < 0.5W /115V	I/P : 230VAC I/P : 115VAC O/P : Min LOAD Ta : 25°C	< 0.46 W < 0.34 W	P

PROTECTION FUNCTION TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	OVER LOAD PROTECTION	105% ~ 135 %	I/P : 230 VAC I/P : 115 VAC O/P : TESTING Ta : 25°C	119 %/ 230 VAC 119 %/ 115 VAC Hiccup Mode	P
2	OVER VOLTAGE PROTECTION	CH1 : 27.6 V ~ 32.4 V	I/P : 230 VAC I/P : 115 VAC O/P : MIN LOAD Ta : 25°C	30.46 V/ 230 VAC 30.39 V/ 115 VAC Shut down Re- power ON	P
3	SHORT PROTECTION	SHORT EVERY OUTPUT 1 HOUR NO DAMAGE	I/P : 264 VAC O/P : FULL LOAD Ta : 25°C	NO DAMAGE Hiccup Mode	P

COMPONENT STRESS TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	Power Transistor (D to S) or (C to E) Peak Voltage	Q 3 Rated : STP10NK70ZFP 10A/700V	I/P : High-Line +3V = 267 V O/P : (1)Full Load Turn on (2) Output Short (3)Full load continue Ta : 25°C	(1) 576 V (2) 472 V (3) 560 V	P
2	Diode Peak Voltage	Q101 Rated : YA868C15RSC 30A/150V	I/P : High-Line +3V = 267 V O/P : (1)Full Load Turn on (2)Output Short (3)Full load continue Ta : 25°C	(1) 139 V (2) 119 V (3) 126 V	P
3	Clamp Diode Peak Voltage	D 2 Rated : 3A/600V GP30J	I/P : High-Line +3V = 267 V O/P : (1) Dynamic Load 90%Duty/1KHz (2)Full load continue Ta : 25°C	(1) 512 V (2) 514 V	P
4	Input Capacitor Voltage	C5 Rated : 100u/420V 105°C 18*30 PAG	I/P : High-Line +3V = 267 V O/P : (1)Full Load Turn on /Off (2) Min load Turn on /Off (3)Full Load /Min load Change Ta : 25°C	(1) 393.3 V (2) 378.3 V (3) 377.1 V	P
5	Control IC Voltage Test	U1 Rated : PFC FAN6921MR 11V~30V	I/P : High-Line +3V = 267 V O/P : (1)Full Load Turn on /Off (2) Min load Turn on /Off (3)Full Load /Min load Change Ta : 25°C	(1) 20.60 V (2) 20.60 V (3) 20.61 V	P
6	Power Transistor (D to S) or (C to E) Peak Voltage	Q1 Rated : 2SK4106 12A/500V	I/P : High-Line +3V = 267 V O/P : (1)Full Load Turn on (2) Output Short (3)Full load continue Ta : 25°C	(1) 434 V (2) 402 V (3) 406 V	P

■ SAFETY & E.M.C. TEST

SAFETY TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	WITHSTAND VOLTAGE	I/P-O/P : 3 KVAC/min I/P-FG : 1.5 KVAC/min O/P-FG : 0.5 KVAC/min	I/P-O/P : 3.6 KVAC/min I/P-FG : 1.8 KVAC/min O/P-FG : 0.6 KVAC/min Ta : 25°C	I/P-O/P : 5.26 mA I/P-FG : 3.83 mA O/P-FG : 7.97 mA NO DAMAGE	P
2	ISOLATION RESISTANCE	I/P-O/P : 500VDC>100MΩ I/P-FG : 500VDC>100MΩ O/P-FG : 500VDC>100MΩ	I/P-O/P : 500 VDC I/P-FG : 500 VDC O/P-FG : 500 VDC Ta : 25°C / 70%RH	I/P-O/P : 30 GΩ I/P-FG : 30 GΩ O/P-FG : 29 GΩ NO DAMAGE	P
3	GROUNDING CONTINUITY	FG(PE) TO CHASSIS OR TRACE < 100 mΩ	40 A / 2min Ta : 25°C / 70%RH	11 mΩ	P
4	APPROVAL	TUV : Certificate NO : R50175193 UL : File NO : E183223			P

E.M.C TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	HARMONIC	EN61000-3-2 CLASS A CLASS D	I/P : 230/240/220 VAC/50HZ O/P : 100/75/50/25% LOAD Ta : 25°C	PASS	P
2	CONDUCTION	EN55022 CLASS B	I/P : 230 V (50HZ)/115V(60HZ) O/P : FULL/50% LOAD Ta : 25°C	PASS Test by certified Lab	P
3	RADIATION	EN55022 CLASS B	I/P : 230 V (50HZ)/115V(60HZ) O/P : FULL LOAD Ta : 25°C	PASS Test by certified Lab	P
4	E.S.D	EN61000-4-2 INDUSTRY AIR : 8KV / Contact : 4KV	I/P : 230 VAC/50HZ O/P : FULL LOAD Ta : 25°C	CRITERIA A	P
5	E.F.T	EN61000-4-4 INDUSTRY INPUT : 2KV	I/P : 230 VAC/50HZ O/P : FULL LOAD Ta : 25°C	CRITERIA A	P
6	SURGE	IEC61000-4-5 INDUSTRY L-N : 2KV L,N-PE : 4KV	I/P : 230 VAC/50HZ O/P : FULL LOAD Ta : 25°C	CRITERIA A	P
7	Test by certified Lab & Test Report Prepare				

		MODEL : ELP-75-12 WITH CASE																																																																																																																											
		1. ROOM AMBIENT BURN-IN : 12 HRS I/P : 230VAC O/P : FULL LOAD Ta= 27.1 °C																																																																																																																											
		2. HIGH AMBIENT BURN-IN : 2 HRS I/P : 230VAC O/P : FULL LOAD Ta= 51.1 °C																																																																																																																											
		<table><tr><th>NO</th><th>Position</th><th>P/N</th><th>ROOM AMBIENT Ta= 27.1 °C</th><th>HIGH AMBIENT Ta= 51.1 °C</th></tr><tr><td>1</td><td>LF2</td><td>TR929</td><td>43.7°C</td><td>63.5°C</td></tr><tr><td>2</td><td>L3</td><td>TF2083</td><td>54.9°C</td><td>74.0°C</td></tr><tr><td>3</td><td>L1</td><td>TR928</td><td>51.8°C</td><td>71.6°C</td></tr><tr><td>4</td><td>T1</td><td>TF2086</td><td>68.9°C</td><td>88.4°C</td></tr><tr><td>5</td><td>Q1</td><td>2SK4106 12A/500V</td><td>51.5°C</td><td>72.4°C</td></tr><tr><td>6</td><td>Q3</td><td>STP10NK70ZFP 10A/700V</td><td>55.9°C</td><td>77.2°C</td></tr><tr><td>7</td><td>D1</td><td>MUR460 4A/600V</td><td>60.1°C</td><td>80.4°C</td></tr><tr><td>8</td><td>D2</td><td>2A/800V GP20K</td><td>74.8°C</td><td>97.1°C</td></tr><tr><td>9</td><td>R9</td><td>TVS P6KE300A</td><td>70.8°C</td><td>91.8°C</td></tr><tr><td>10</td><td>C5</td><td>100u/420V 105°C 18*30 PAG</td><td>54.9°C</td><td>75.6°C</td></tr><tr><td>11</td><td>C61</td><td>33u/50V L5Kh 6.3*11 KY</td><td>53.9°C</td><td>75.1°C</td></tr><tr><td>12</td><td>C18</td><td>22u/50V L5Kh 5*11 KY</td><td>54.6°C</td><td>75.9°C</td></tr><tr><td>13</td><td>C150</td><td>100u/25V UL10Kh 6.3*11 YXM</td><td>46.6°C</td><td>67.7°C</td></tr><tr><td>14</td><td>C151</td><td>100u/25V UL10Kh 6.3*11 YXM</td><td>44.1°C</td><td>66.0°C</td></tr><tr><td>15</td><td>C105</td><td>820u/25V UL10Kh 10*20 ZLH</td><td>47.6°C</td><td>69.3°C</td></tr><tr><td>16</td><td>C106</td><td>820u/25V UL10Kh 10*20 ZLH</td><td>48.5°C</td><td>69.9°C</td></tr><tr><td>17</td><td>C107</td><td>820u/25V UL10Kh 10*20 ZLH</td><td>47.1°C</td><td>69.1°C</td></tr><tr><td>18</td><td>C109</td><td>820u/25V UL10Kh 10*20 ZLH</td><td>46.6°C</td><td>68.1°C</td></tr><tr><td>19</td><td>C110</td><td>820u/25V UL10Kh 10*20 ZLH</td><td>45.8°C</td><td>67.6°C</td></tr><tr><td>20</td><td>C111</td><td>470u/25V L7Kh 10*16 YXG</td><td>44.4°C</td><td>66.4°C</td></tr><tr><td>21</td><td>Q102</td><td>IRFB3607PBF 80A/75V</td><td>53.8°C</td><td>74.9°C</td></tr><tr><td>22</td><td>BD1</td><td>4A/800V GLASS GBU408</td><td>48.2°C</td><td>68.4°C</td></tr><tr><td>23</td><td>U1</td><td>PFC FAN6921MR</td><td>67.3°C</td><td>88.1°C</td></tr></table>			NO	Position	P/N	ROOM AMBIENT Ta= 27.1 °C	HIGH AMBIENT Ta= 51.1 °C	1	LF2	TR929	43.7°C	63.5°C	2	L3	TF2083	54.9°C	74.0°C	3	L1	TR928	51.8°C	71.6°C	4	T1	TF2086	68.9°C	88.4°C	5	Q1	2SK4106 12A/500V	51.5°C	72.4°C	6	Q3	STP10NK70ZFP 10A/700V	55.9°C	77.2°C	7	D1	MUR460 4A/600V	60.1°C	80.4°C	8	D2	2A/800V GP20K	74.8°C	97.1°C	9	R9	TVS P6KE300A	70.8°C	91.8°C	10	C5	100u/420V 105°C 18*30 PAG	54.9°C	75.6°C	11	C61	33u/50V L5Kh 6.3*11 KY	53.9°C	75.1°C	12	C18	22u/50V L5Kh 5*11 KY	54.6°C	75.9°C	13	C150	100u/25V UL10Kh 6.3*11 YXM	46.6°C	67.7°C	14	C151	100u/25V UL10Kh 6.3*11 YXM	44.1°C	66.0°C	15	C105	820u/25V UL10Kh 10*20 ZLH	47.6°C	69.3°C	16	C106	820u/25V UL10Kh 10*20 ZLH	48.5°C	69.9°C	17	C107	820u/25V UL10Kh 10*20 ZLH	47.1°C	69.1°C	18	C109	820u/25V UL10Kh 10*20 ZLH	46.6°C	68.1°C	19	C110	820u/25V UL10Kh 10*20 ZLH	45.8°C	67.6°C	20	C111	470u/25V L7Kh 10*16 YXG	44.4°C	66.4°C	21	Q102	IRFB3607PBF 80A/75V	53.8°C	74.9°C	22	BD1	4A/800V GLASS GBU408	48.2°C	68.4°C	23	U1	PFC FAN6921MR	67.3°C	88.1°C	
NO	Position	P/N	ROOM AMBIENT Ta= 27.1 °C	HIGH AMBIENT Ta= 51.1 °C																																																																																																																									
1	LF2	TR929	43.7°C	63.5°C																																																																																																																									
2	L3	TF2083	54.9°C	74.0°C																																																																																																																									
3	L1	TR928	51.8°C	71.6°C																																																																																																																									
4	T1	TF2086	68.9°C	88.4°C																																																																																																																									
5	Q1	2SK4106 12A/500V	51.5°C	72.4°C																																																																																																																									
6	Q3	STP10NK70ZFP 10A/700V	55.9°C	77.2°C																																																																																																																									
7	D1	MUR460 4A/600V	60.1°C	80.4°C																																																																																																																									
8	D2	2A/800V GP20K	74.8°C	97.1°C																																																																																																																									
9	R9	TVS P6KE300A	70.8°C	91.8°C																																																																																																																									
10	C5	100u/420V 105°C 18*30 PAG	54.9°C	75.6°C																																																																																																																									
11	C61	33u/50V L5Kh 6.3*11 KY	53.9°C	75.1°C																																																																																																																									
12	C18	22u/50V L5Kh 5*11 KY	54.6°C	75.9°C																																																																																																																									
13	C150	100u/25V UL10Kh 6.3*11 YXM	46.6°C	67.7°C																																																																																																																									
14	C151	100u/25V UL10Kh 6.3*11 YXM	44.1°C	66.0°C																																																																																																																									
15	C105	820u/25V UL10Kh 10*20 ZLH	47.6°C	69.3°C																																																																																																																									
16	C106	820u/25V UL10Kh 10*20 ZLH	48.5°C	69.9°C																																																																																																																									
17	C107	820u/25V UL10Kh 10*20 ZLH	47.1°C	69.1°C																																																																																																																									
18	C109	820u/25V UL10Kh 10*20 ZLH	46.6°C	68.1°C																																																																																																																									
19	C110	820u/25V UL10Kh 10*20 ZLH	45.8°C	67.6°C																																																																																																																									
20	C111	470u/25V L7Kh 10*16 YXG	44.4°C	66.4°C																																																																																																																									
21	Q102	IRFB3607PBF 80A/75V	53.8°C	74.9°C																																																																																																																									
22	BD1	4A/800V GLASS GBU408	48.2°C	68.4°C																																																																																																																									
23	U1	PFC FAN6921MR	67.3°C	88.1°C																																																																																																																									
3	OVER LOAD BURN-IN TEST	NO DAMAGE 1 HOUR (MIN)	I/P : 230 VAC O/P : 123 % LOAD Ta : 25°C	TEST : OK	P																																																																																																																								
4	LOW TEMPERATURE TURN ON TEST	TURN ON AFTER 2 HOUR	I/P : 264VAC/100VAC O/P : 100 % LOAD Ta= -30 °C	TEST : OK	P																																																																																																																								
5	HIGH HUMIDITY HIGH TEMPERATURE HIGH VOLTAGE TURN ON TEST	AFTER 12 HOURS IN CHAMBER ON CONTROL 50 °C NO DAMAGE	I/P : 272 VAC O/P : FULL LOAD Ta= 50 °C HUMIDITY= 95 %R.H	TEST : OK	P																																																																																																																								
6	TEMPERATURE COEFFICIENT	± 0.03 % (0~50°C)	I/P : 230 VAC O/P : FULL LOAD	± 0.1 % (0~50°C)	P																																																																																																																								
7	STORAGE TEMPERATURE TEST	1. Thermal shock Temperature : -45°C~ +90°C 2. Temperature change rate : 25°C / MIN 3. Dwell time low and high temperature : 30 MIN/EACH 4. Total test cycle : 5 CYCLE 5. Input/Output condition : STATIC		OK	P																																																																																																																								

8.	THERMAL SHOCK TEST	1. Thermal shock Temperature : $-30^{\circ}\text{C} \sim +50^{\circ}\text{C}$ 2. Temperature change rate : $25^{\circ}\text{C} / \text{MIN}$ 3. Dwell time low and high temperature : 30 MIN/EACH 4. Total test cycle : 10 CYCLE 5. Input/Output condition : 230VAC/Full Load AC ON/OFF TEST turn on 58sec ; turn off 2sec	OK	P
9	VIBRATION TEST	1 Carton & 1 Set (1) Waveform : Sine Wave (2) Frequency : 10~500Hz (3) Sweep Time : 10min/sweep cycle (4) Acceleration : 2G (5) Test Time : 60min in each axis (X.Y.Z) (6) Ta : 25°C	TEST : OK	P
10	CAPACITOR LIFE CYCLE	ELP-75-12 PCB ONLY SUPPOSE C105 IS THE MOST CRITICAL COMPONENT (1) I/P : 230VAC O/P : FULL LOAD Ta= 25°C LIFE TIME (2) I/P : 230VAC O/P : FULL LOAD Ta= 50°C LIFE TIME (3) I/P : 230VAC O/P : 75% LOAD Ta= 50°C LIFE TIME ELP-75-12 WITH CASE SUPPOSE C105 IS THE MOST CRITICAL COMPONENT (1) I/P : 230VAC O/P : FULL LOAD Ta= 25°C LIFE TIME (2) I/P : 230VAC O/P : FULL LOAD Ta= 50°C LIFE TIME (3) I/P : 230VAC O/P : 75% LOAD Ta= 50°C LIFE TIME	(1) 685924.8HRS (2) 163332.3HRS (3) 187660.9HRS (1) 685344HRS (2) 145140HRS (3) 183608HRS	P
11	MTBF	MIL-HDBK-217F NOTICES2 PARTS COUNT TOTAL FAILURE RATE : 345.3K HRS		P

DATE	SAMPLE	TEST RESULT	TESTER	APPROVAL
2009/12/17	RD SAMPLE	PASS	SANFORD SU	VINCENT TSENG
2010/1/21	PRODUCT SAMPLE W1001A26	PASS	SANFORD SU	VINCENT TSENG

2009/08/04 A50-F023