

Model : GS06x-6 6W AC-DC Single Output Wall-mount adaptor
V1 : +24V / 0.25A

OUTPUT FUNCTION TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	RIPPLE & NOISE	180mVp-p (Typ)	I/P:230VAC O/P:FULL LOAD Ta:25°C	15mVp-p	P
2	VOLTAGE TOLERANCE	-2% ~ +2% (Max)	I/P:90VAC~264VAC O/P:FULL~MIN. LOAD Ta:25°C	-1.0% ~ +0%	P
3	LINE REGULATION	-0.5% ~ +0.5% (Max)	I/P:90VAC ~264VAC O/P:FULL LOAD Ta:25°C	-0% ~ +0%	P
4	LOAD REGULATION	-2% ~ +2% (Max)	I/P:230VAC O/P:FULL ~MIN LOAD Ta:25°C	-0.1% ~ +0.1%	P
5	SET UP TIME	1000mS (Max)	I/P:230VAC O/P:FULL LOAD Ta:25°C	520 mS	P
6	RISE TIME	50mS (Max)	I/P:230VAC O/P:FULL LOAD Ta:25°C	10.6 mS	P
7	HOLD UP TIME	12mS (Min)	I/P:115VAC O/P:FULL LOAD Ta:25°C	18.15 mS	P

INPUT FUNCTION TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	VOLTAGE RANGE	100VAC ~ 240VAC (Typ)	I/P:TESTING O/P:FULL LOAD Ta:25°C	40V ~ 264V	P
2	FREQUENCY RANGE	50HZ - 60HZ (Typ) NO DAMAGE OSC	I/P: 100VAC ~ 240VAC O/P:FULL~MIN LOAD Ta:25°C	TEST: OK	P
3	EFFICIENCY	80% (Typ)	I/P:230VAC O/P:FULL LOAD Ta:25°C	83.59%	P
4	AC CURRENT	0.2A (Max)	I/P: 100VAC O/P:FULL LOAD Ta:25°C	0.13A	P
5	NO LOAD POWER	< 0.75W	I/P:230VAC O/P: NO LOAD Ta:25°C	0.3W (230VAC)	P

6	INRUSH CURRENT	< 50A COLD START	I/P:230VAC O/P:FULL LOAD Ta:25°C	43.9A	P
7	LEAKAGE CURRENT	<0.25mA / 240VAC	I/P:240VAC O/P:Min LOAD Ta:25°C	0.002mA	P

PROTECTION FUNCTION TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	OVER LOAD PROTECTION	>120%	I/P:230VAC O/P:TESTING Ta:25°C	304% HICCUP MODE RESET AUTO RECOVER	P
2	OVER VOLTAGE PROTECTION	>120% CLAMP BY ZENER DIODE	I/P:230VAC O/P:MIN LOAD Ta:25°C	CLAMP BY ZENER DIODE	P
3	SHORT PROTECTION	SHORT EVERY OUTPUT 1 HOUR NO DAMAGE	I/P:264VAC O/P:FULL LOAD Ta:25°C	NO DAMAGE HICCUP MODE RESET AUTO RECOVER	P

ENVIRONMENT TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDICT
1	TEMPERATURE RISE TEST	1. ROOM AMBIENT BURN-IN : 4HRS I/P:230VAC O/P:100% LOAD Ta=29.0°C 2. ROOM AMBIENT BURN-IN : 2HRS I/P:115VAC O/P:100% LOAD Ta=29.0°C 3. ROOM AMBIENT BURN-IN : 2HRS I/P:115VAC O/P:100% LOAD Ta=44.0°C 4. ROOM AMBIENT BURN-IN : 2HRS I/P:230VAC O/P:100% LOAD Ta=44.5°C			P

SAFETY & E.M.C TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	SAFETY STANDARDS	TUV: Certificate NO : S 50064872 UL: File NO : E206808			P
2	HARMONIC	IEC61000-3-2 CLASS A	I/P:230VAC / 50HZ O/P:FULL LOAD Ta:25°C	PASS	P
3	CONDUCTION	EN55022 CLASS B	I/P:230VAC (50HZ) O/P:FULL LOAD Ta:25°C	PASS	P
4	RADIATION	EN55022 CLASS B	I/P:230VAC (50HZ) O/P:FULL LOAD Ta:25°C	PASS	P
5	E.S.D	IEC61000-4-2 LIGHT INDUSTRY AIR:8KV / Contact:4KV	I/P:230VAC/50HZ O/P:FULL LOAD Ta:25°C	CRITERIA A	P
6	E.F.T	IEC61000-4-4 LIGHT INDUSTRY INPUT: 1KV	I/P:230VAC/50HZ O/P:FULL LOAD Ta:25°C	CRITERIA A	P
7	SURGE	IEC61000-4-5 LIGHT INDUSTRY L-N :1KV	I/P:230VAC/50HZ O/P:FULL LOAD Ta:25°C	CRITERIA A	P
8	WITHSTAND VOLTAGE	I/P-O/P:4242VDC/min	I/P-O/P:4242VDC/min Ta:25°C	I/P-O/P:0.02mA NO DAMAGE	P
9	ISOLATION RESISTANCE	I/P-O/P:500VDC>50MΩ	I/P-O/P:500VDC Ta:25°C	I/P-O/P:>100MΩ NO DAMAGE	P

OTHER

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	CAPACITOR LIFE CYCLE	SUPPOSE C9 IS THE MOST CRITICAL COMPONENT I/P:230 VAC O/P:FULL LOAD Ta=25°C LIFE TIME=97005HRS I/P:230 VAC O/P:FULL LOAD Ta=40°C LIFE TIME=39946HRS			P
2	MTBF	MIL-HDBK-217F NOTICES2 PARTS COUNT TOTAL FAILURE RATE: 1.850090 M.T.B.F: 540514HRS			P

DATE	SAMPLE	TEST RESULT	TESTER	APPROVAL
2007.1.25	GS06x-6	PASS	T.K.CHENG	MAX LIN