



Test Report: IRM-15-24

15W Single Output Encapsulated Type

■ DESIGN VERIFY TEST

Output Function Test

Input Function Test

Protection Function Test

Control Function Test

Component Stress Test

■ SAFETY & E.M.C. TEST

Safety Test

E.M.C. Test

■ RELIABILITY TEST

ENVIRONMENT TEST

DESIGN VERIFY TEST

OUTPUT FUNCTION TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	RIPPLE & NOISE	V1 : 200 mVp-p (Max)	I/P : 230VAC O/P : FULL LOAD Ta : 25°C	V1 : 55.6 mVp-p (Max)	P
2	OUTPUT VOLTAGE TOLERANCE	V1 : -2.5 % ~ +2.5 % (Max)	I/P : 115 VAC / 264 VAC O/P : FULL / MIN LOAD Ta : 25°C	V1 : -0.16 % ~ 0.26 %	P
3	LINE REGULATION	V1 : -0.3 % ~ +0.3 % (Max)	I/P : 115VAC ~ 264 VAC O/P : FULL LOAD Ta : 25°C	V1 : -0.025 % ~ 0.179 %	P
4	LOAD REGULATION	V1 : -0.5 % ~ +0.5 % (Max)	I/P : 230 VAC O/P : FULL ~ MIN LOAD Ta : 25°C	V1 : -0.13 % ~ 0.26 %	P
5	SET UP TIME	230VAC : 1000 ms (Max) 115VAC : 1000 ms(Max)	I/P : 230 VAC I/P : 115 VAC O/P : FULL LOAD Ta : 25°C	230VAC/ 709 ms 115VAC/ 595 ms	P
6	RISE TIME	230VAC : 20 ms (Max) 115VAC : 20 ms (Max)	I/P : 230 VAC I/P : 115 VAC O/P : FULL LOAD Ta : 25°C	230VAC/ 13.3 ms 115VAC/ 14.1 ms	P
7	HOLD UP TIME	230VAC : 40 ms (TYP) 115VAC : 10 ms (TYP)	I/P : 230 VAC I/P : 115 VAC O/P : FULL LOAD Ta : 25°C	230VAC/ 82.8 ms 115VAC/ 16.5 ms	P
8	OVER/UNDERSHOOT TEST	< ±5%	I/P : 230 VAC O/P : FULL LOAD Ta : 25°C	TEST : <5 %	P
9	DYNAMIC LOAD	V1 : 2400 mVp-p	I/P : 230 VAC (1).O/P : FULL /Min LOAD 90%DUTY/ 1KHZ (2).O/P : FULL /Min LOAD 90%DUTY/ 3KHZ (3).O/P : FULL /Min LOAD 90%DUTY/ 5KHZ (4).O/P : FULL /Min LOAD 50%DUTY/ 120HZ Ta : 25°C	(1) 238 mVp-p (2) 128 mVp-p (3) 106 mVp-p (4) 526 mVp-p	P

INPUT FUNCTION TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	INPUT VOLTAGE RANGE	85VAC~264 VAC	I/P : TESTING O/P : FULL LOAD Ta : 25°C	70.8 V~264V	P
			I/P : LOW-LINE-3V= 82 V HIGH-LINE+15%=300 V O/P : FULL/MIN LOAD ON : 30 Sec. OFF : 30 Sec 10MIN (AC POWER ON/OFF NO DAMAGE)	TEST : OK	
2	INPUT FREQUENCY RANGE	47HZ ~440 HZ NO DAMAGE OSC	I/P : 85 VAC ~ 264 VAC O/P : FULL~MIN LOAD Ta : 25°C	TEST : OK	P
3	EFFICIENCY	83% (TYP)	I/P : 230 VAC O/P : FULL LOAD Ta : 25°C	86.25 %	P
4	INPUT CURRENT	230V/ 0.2 A (TYP) 115V/ 0.35 A (TYP)	I/P : 230 VAC I/P : 115 VAC O/P : FULL LOAD Ta : 25°C	I = 0.15 A/ 230 VAC I = 0.25 A/ 115 VAC	P
5	INRUSH CURRENT	230V/ 40 A (TYP) COLD START	I/P : 230 VAC O/P : FULL LOAD Ta : 25°C	I = 26.2 A/ 230 VAC	P
6	LEAKAGE CURRENT	< 0.25 mA/240 VAC	I/P : 240 VAC O/P : Min LOAD Ta : 25°C	L-FG : 0.016 mA N-FG : 0.016 mA	P
7	NO LOAD CONSUMPTION	< 0.1 W	I/P : 240VAC O/P : NO LOAD Ta : 25°C	< 0.0853 W	P

PROTECTION FUNCTION TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	OVER LOAD PROTECTION	115 % ~ 190 %	I/P : 230 VAC I/P : 115 VAC O/P : TESTING Ta : 25°C	136.8 %/ 230 VAC 127.9 %/ 115 VAC Hiccup Mode	P
2	OVER VOLTAGE PROTECTION	CH1 : 27.6 V ~ 32.4 V	O/P : MIN LOAD Ta : 25°C	29.92 V shut down clamping by zener diode	P
3	SHORT PROTECTION	SHORT EVERY OUTPUT 1 HOUR NO DAMAGE	I/P : 264 VAC O/P : FULL LOAD Ta : 25°C	NO DAMAGE Hiccup Mode	P

COMPONENT STRESS TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	Power Transistor DRAIN TO GND Peak Voltage	U1 Rated: 800 V 1.5 A	I/P : High-Line +3V = 267 V O/P : (1)Full Load Turn on (2) Output Short (3)Full load continue Ta : 25℃	(1) 506 V (2) 516 V (3) 500 V	P
2	Diode Peak Voltage	D100 Rated: 20 A 300 V	I/P : High-Line +3V = 267 V O/P : (1)Full Load Turn on (2)Output Short (3)Full load continue Ta : 25℃	(1) 146 V (2) 143 V (3) 145 V	P
3	Clamp Diode Peak Voltage	D 2 Rated : 800 V 2 A	I/P : High-Line +3V = 267 V O/P : (1) Dynamic Load 90%Duty/1KHz (2)Full load continue Ta : 25℃	(1) 483 V (2) 476 V	P
4	Input Capacitor Voltage	C5 Rated: 27u/400V 105℃	I/P : High-Line +3V = 267 V O/P : (1)Full Load Turn on /Off (2) Min load Turn on /Off (3)Full Load /Min load Change Ta : 25℃	(1) 368 V (2) 368 V (3) 372 V	P
5	Control IC Voltage Test	U1 Rated : 27 V	I/P : High-Line +3V = 267 V O/P : (1)Full Load Turn on /Off (2) Min load Turn on /Off (3)Full Load /Min load Change Ta : 25℃	(1) 17.6 V (2) 16.9 V (3) 17.6 V	P

■ SAFETY & E.M.C. TEST

SAFETY TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	WITHSTAND VOLTAGE	I/P-O/P : 3 KVAC/min	I/P-O/P : 3.6 KVAC/min Ta : 25°C	I/P-O/P : 0.513 mA NO DAMAGE	P
2	ISOLATION RESISTANCE	I/P-O/P : 500VDC>100MΩ	I/P-O/P : 500 VDC Ta : 25°C/70%RH	I/P-O/P : 9999 MΩ NO DAMAGE	P

E.M.C TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	HARMONIC	EN61000-3-2 CLASS B	I/P : 230 VAC/50HZ O/P : FULL LOAD Ta : 25°C	PASS	P
2	CONDUCTION	EN55022 CLASS B	I/P : 230 VAC (50HZ) O/P : FULL/50% LOAD Ta : 25°C	PASS Test by certified Lab	P
3	RADIATION	EN55022 CLASS B	I/P : 230 VAC (50HZ) O/P : FULL LOAD Ta : 25°C	PASS Test by certified Lab	P
4	E.S.D	EN61000-4-2 INDUSTRY AIR : 8KV / Contact : 4KV	I/P : 230 VAC/50HZ O/P : FULL LOAD Ta : 25°C	CRITERIA A	P
5	E.F.T	EN61000-4-4 INDUSTRY INPUT : 2KV	I/P : 230 VAC/50HZ O/P : FULL LOAD Ta : 25°C	CRITERIA A	P
6	SURGE	IEC61000-4-5 INDUSTRY L-N : 1KV	I/P : 230 VAC/50HZ O/P : FULL LOAD Ta : 25°C	CRITERIA A	P
7	Test by certified Lab & Test Report Prepare				

RELIABILITY TEST

ENVIRONMENT TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT																																																												
1	TEMPERATURE RISE TEST	MODEL : IRM-15-24 1. ROOM AMBIENT BURN-IN : 2 HRS I/P : 230VAC O/P : FULL LOAD Ta=23.3 °C 2. HIGH AMBIENT BURN-IN : 2 HRS I/P : 230VAC O/P : FULL LOAD Ta= 49.1°C <table><tr><th>NO</th><th>Position</th><th>PART NUMBER</th><th>ROOM AMBIENT Ta= 23.3°C</th><th>HIGH AMBIENT Ta= 49.1°C</th></tr><tr><td>1</td><td>LF1</td><td>LF LF512-R0 UU9.8 0.4A 35.84mH B</td><td>47.5°C</td><td>72.8°C</td></tr><tr><td>2</td><td>C5</td><td>27u/400V 105°C 12.5*20 KXJ IIR</td><td>50.9°C</td><td>76.0°C</td></tr><tr><td>3</td><td>D2</td><td>FRD 1A/1KV FR107 T-52mm</td><td>58.2°C</td><td>83.3°C</td></tr><tr><td>4</td><td>U1</td><td>PWM ICE3AR2280CJZ</td><td>62.9°C</td><td>88.6°C</td></tr><tr><td>5</td><td>T1coil</td><td>MT TF2539 RM6</td><td>54.2°C</td><td>79.0°C</td></tr><tr><td>6</td><td>T1core</td><td>MT TF2539 RM6</td><td>54.9°C</td><td>79.5°C</td></tr><tr><td>7</td><td>D100</td><td>SFRD STTH2003CT 20A/300V TO220</td><td>57.8°C</td><td>81.3°C</td></tr><tr><td>8</td><td>C101</td><td>C/E 330u/35V UL10Kh 10*12.5 ZLH</td><td>47.9°C</td><td>72.8°C</td></tr><tr><td>9</td><td>BD1</td><td>SMD BD 2A/800V TT208</td><td>56.8°C</td><td>81.5°C</td></tr><tr><td>10</td><td>D3</td><td>SMD SFRD FM4007M-TG 1A/1KV</td><td>64.3°C</td><td>89.4°C</td></tr><tr><td>11</td><td>CASE</td><td>1**1219A-T</td><td>37.9°C</td><td>64.2°C</td></tr></table>			NO	Position	PART NUMBER	ROOM AMBIENT Ta= 23.3°C	HIGH AMBIENT Ta= 49.1°C	1	LF1	LF LF512-R0 UU9.8 0.4A 35.84mH B	47.5°C	72.8°C	2	C5	27u/400V 105°C 12.5*20 KXJ IIR	50.9°C	76.0°C	3	D2	FRD 1A/1KV FR107 T-52mm	58.2°C	83.3°C	4	U1	PWM ICE3AR2280CJZ	62.9°C	88.6°C	5	T1coil	MT TF2539 RM6	54.2°C	79.0°C	6	T1core	MT TF2539 RM6	54.9°C	79.5°C	7	D100	SFRD STTH2003CT 20A/300V TO220	57.8°C	81.3°C	8	C101	C/E 330u/35V UL10Kh 10*12.5 ZLH	47.9°C	72.8°C	9	BD1	SMD BD 2A/800V TT208	56.8°C	81.5°C	10	D3	SMD SFRD FM4007M-TG 1A/1KV	64.3°C	89.4°C	11	CASE	1**1219A-T	37.9°C	64.2°C	P
NO	Position	PART NUMBER	ROOM AMBIENT Ta= 23.3°C	HIGH AMBIENT Ta= 49.1°C																																																													
1	LF1	LF LF512-R0 UU9.8 0.4A 35.84mH B	47.5°C	72.8°C																																																													
2	C5	27u/400V 105°C 12.5*20 KXJ IIR	50.9°C	76.0°C																																																													
3	D2	FRD 1A/1KV FR107 T-52mm	58.2°C	83.3°C																																																													
4	U1	PWM ICE3AR2280CJZ	62.9°C	88.6°C																																																													
5	T1coil	MT TF2539 RM6	54.2°C	79.0°C																																																													
6	T1core	MT TF2539 RM6	54.9°C	79.5°C																																																													
7	D100	SFRD STTH2003CT 20A/300V TO220	57.8°C	81.3°C																																																													
8	C101	C/E 330u/35V UL10Kh 10*12.5 ZLH	47.9°C	72.8°C																																																													
9	BD1	SMD BD 2A/800V TT208	56.8°C	81.5°C																																																													
10	D3	SMD SFRD FM4007M-TG 1A/1KV	64.3°C	89.4°C																																																													
11	CASE	1**1219A-T	37.9°C	64.2°C																																																													
2	OVER LOAD BURN-IN TEST	NO DAMAGE 1 HOUR (MIN)	I/P : 230 VAC O/P : 127 % LOAD Ta : 25°C	TEST : OK	P																																																												
3	LOW TEMPERATURE TURN ON TEST	TURN ON AFTER 2 HOUR	I/P : 264VAC/85VAC O/P : 100 % LOAD Ta= -30 °C	TEST : OK	P																																																												
4	HIGH HUMIDITY HIGH TEMPERATURE HIGH VOLTAGE TURN ON TEST	AFTER 12 HOURS IN CHAMBER ON CONTROL 50 °C NO DAMAGE	I/P : 272 VAC O/P : FULL LOAD Ta= 50 °C HUMIDITY= 95 %R.H	TEST : OK	P																																																												
5	TEMPERATURE COEFFICIENT	± 0.03 %/°C (0~50°C)	I/P : 230 VAC O/P : FULL LOAD	± 0.006 %/°C (0~50°C)	P																																																												
6	STORAGE TEMPERATURE TEST	1. Thermal shock Temperature : -40°C~ +85°C 2. Temperature change rate : 25°C / MIN 3. Dwell time low and high temperature : 30 MIN/EACH 4. Total test cycle : 5 CYCLE 5. Input/Output condition : STATIC		OK	P																																																												

7	THERMAL SHOCK TEST	1. Thermal shock Temperature : -30°C ~ +70°C 2. Temperature change rate : 25°C / MIN 3. Dwell time low and high temperature : 30 MIN/EACH 4. Total test cycle : 10 CYCLE 5. Input/Output condition : 230VAC/Full Load AC ON/OFF TEST turn on 58sec ; turn off 2sec	OK	P
8	VIBRATION TEST	1 Carton & 1 Set (1) Waveform : Sine Wave (2) Frequency : 10~500Hz (3) Sweep Time : 12min/sweep cycle (4) Acceleration : 5G (5) Test Time : 60min in each axis (X.Y.Z) (6) Ta : 25°C	TEST : OK	P
9	CAPACITOR LIFE CYCLE	IRM-15-24 PCB ONLY SUPPOSE C 101 IS THE MOST CRITICAL COMPONENT (1) I/P : 230VAC O/P : FULL LOAD Ta= 25 °C LIFE TIME (2) I/P : 230VAC O/P : FULL LOAD Ta=50 °C LIFE TIME (3) I/P : 230VAC O/P : 75% LOAD Ta= 50 °C LIFE TIME (4) I/P : 230VAC O/P : 50% LOAD Ta= 50 °C LIFE TIME	(1) 559755 HRS (2) 105262 HRS (3) 157472 HRS (4) 202104 HRS	P
10	MTBF	MIL-HDBK-217F NOTICE S2 PARTS COUNT TOTAL FAILURE RATE : 970.3 KHRS		P
11	DMTBF/Accelerated Life Test	Demonstration Mean Time Between Failure (Expected Life): Above 30,000 hours @ TA 50°C		P

DATE	SAMPLE	TEST RESULT	TESTER	APPROVAL
2013.3.26	RD SAMPLE	PASS	Shenym	Wangdz
2013.5.4	PRODUCT SAMPLE	PASS	Shenym	Wangdz
2013.7.11	PRODUCT SAMPLE (Y1306D064)	PASS	Shenym	Wangdz

2007/3/20 A50-S014