







ISI-501 series



500W True Sine Wave DC-AC Inverter with MPPT Solar Charger

ISI-501 series


AC Output Receptacles(Optional)

Receptacle type						
	TYPE-A	TYPE-B	TYPE-C	TYPE-D	TYPE-F	TYPE-U
	Standard	Standard	Optional	Optional	Optional	Optional
Country	USA	EUROPE	AUSTRALIA	U.K	GFCI (60Hz)	UNIVERSAL
Certificate	FC	CE	CE	CE	FC	None



SPECIFICATION

MODEL			ISI-501-112□	ISI-501-124□	ISI-501-148□	ISI-501-212□	ISI-501-224□	ISI-501-248□	
INVERTER SECTION	OUTPUT	RATED POWER	450W	500W		450W	500W		
		MAXIMUM OUTPUT POWER (Typ.)	550W for 60 sec. / surge power 1000W for 30 cycles (112, 212 models : 495W for 60 sec. / surge power 900W for 30 cycles)						
		AC VOLTAGE	Factory setting set at 110VAC 100 / 110 / 115 / 120VAC selectable by setting button S.W				Factory setting set at 230VAC 200 / 220 / 230 / 240VAC selectable by setting button S.W		
		FREQUENCY Note.9	Factory setting set at 110VAC 60±0.1Hz 50/60Hz selectable by setting button S.W				Factory setting set at 230VAC 50±0.1Hz 50/60Hz selectable by setting button S.W		
		WAVEFORM Note.1	True sine wave (THD<3%)						
		AC REGULATION (Typ.)	±3%						
		FRONT PANEL INDICATOR	Fault and operation status, Charger status, Battery capacity						
	INPUT	BAT. VOLTAGE	12V	24V	48V	12V	24V	48V	
		VOLTAGE RANGE Note.3,5	10.5 ~ 15VDC	21 ~ 30VDC	42 ~ 60VDC	10.5 ~ 15VDC	21 ~ 30VDC	42 ~ 60VDC	
		DC CURRENT (Typ.) Note.7	50A	30A	15A	50A	30A	15A	
		NO LOAD CURRENT DRAW (Typ.)	1.25A	0.63A	0.32A	1.25A	0.63A	0.32A	
		OFF MODE CURRENT DRAW (Typ.)	≤1mA						
	OUTPUT PROTECTION	EFFICIENCY (Typ.) Note.2	85%	87%	87%	86%	88%	88%	
		OVER TEMPERATURE	Shut down o/p voltage, re-power on to recover						
		OUTPUT SHORT	Shut down o/p voltage, re-power on to recover						
		OVER LOAD (Typ.)	110% load for 60 sec. Protection type : Shut down o/p voltage, re-power on to recover						
BATTERY SECTION	CHARGER CURRENT (Typ.)	30A	17A	8.5A	30A	17A	8.5A		
	BATTERY TYPE	Open & sealed Lead Acid							
	FUSE	40A*2	40A*1	20A*1	40A*2	40A*1	20A*2		
	BAT. LOW ALARM Note.3	11.3V	22.5V	45V	11.3V	22.5V	45V		
	BAT. LOW SHUTDOWN Note.3	10.5V	21V	42V	10.5V	21V	42V		
	REVERSE POLARITY	By internal fuse open							
MPPT / SOLAR SECTION	MPPT CHARGER EFFICIENCY (Typ.)	98%							
	OPEN CIRCUIT VOLTAGE RANGE	35 ~ 50V	45 ~ 90V	90 ~ 160V	35 ~ 50V	45 ~ 90V	90 ~ 160V		
	MPPT RANGE	25 ~ 50V	35 ~ 90V	70 ~ 160V	25 ~ 50V	35 ~ 90V	70 ~ 160V		
	SOLAR INPUT CURRENT (Typ.)	11A	7A	4.5A	11A	7A	4.5A		
	SOLAR INPUT POWER (Typ.)	500W							
GENERAL SECTION	ENVIRONMENT	WORKING TEMP. Note.4	-20 ~ +40℃ @ 100% load ; 60℃ @ 50% load						
		WORKING HUMIDITY	20% ~ 90% RH non-condensing						
		STORAGE TEMP., HUMIDITY	-30 ~ +70℃ / -22 ~ +158°F, 10 ~ 95% RH non-condensing						
		VIBRATION	10 ~ 500Hz, 3G 10min./1cycle, 60min. each along X, Y, Z axes						
	SAFETY & EMC	SAFETY STANDARDS	IEC62368-1 CB, EAC TP TC 004 approved						
		WITHSTAND VOLTAGE	Bat I/P - AC O/P:3.0KVAC AC O/P - FG:1.5KVAC						
		ISOLATION RESISTANCE	Bat I/P - AC O/P, Bat I/P - FG, AC O/P - FG: 100M ohms / 500VDC / 25℃/ 70% RH						
		EMC EMISSION	Compliance to FCC part 15 class B, EAC TP TC 020				Compliance to EN55032 class B, EAC TP TC 020		
		EMC IMMUNITY	Compliance to EAC TP TC 020				Compliance to EN61000-4-2,3,8, EAC TP TC 020		
	OTHERS	MTBF	57.8K hrs min. MIL-HDBK-217F (25℃)						
DIMENSION		205*158*67mm (L*W*H)							
PACKING		2.35Kg; 6pcs/15.1Kg/1.55CUFT							
NOTE		1.THD is tested by rated power, linear load at 13V,26V,52V input voltage. 2.Efficiency is tested by 350W, linear load at 13V,26V,52V input voltage. 3.The tolerance of each voltage value by models is : 112/212→±0.5V ; 124/224→±1V ; 148/248→±2V. 4.Output derating capacity referenced by curve 1. 5.Input derating capacity referenced by curve 2. 6.All parameters not specified above are measured at rated load, 25℃ of ambient temperature and set to factory setting. 7.DC current is tested by 500W, linear load at 12V,24V,48V input voltage. 8.The ambient temperature derating of 3.5℃/1000m with fanless models and of 5℃/1000m with fan models for operating altitude higher than 2000m(6500ft). 9.Type F for 60Hz only.							


Block Diagram



Derating Curve



Charging Curve



Stage 1 : Constant Current
Stage 2 : Constant Voltage
Stage 3 : MPPT Charger OFF

*Constant current condition : Dependent on solar input current and MPPT voltage of solar panel.

*MPPT charger OFF condition: Charge current less than 10% rated charge current and solar input power under 50W.




Mechanical Specification

Case No.805

Unit:mm


Input Terminal Pin No. Assignment

Pin No.	Assignment	Pin No.	Assignment
1	Battery Input NEG(-)	5	FG $\perp$
2	Battery Input POS(+)	6	Bat. Low Alarm Connector
3	Solar Input NEG(-)	7	Remote ON/OFF Connector
4	Solar Input POS(+)		



Type-A

Function Manual




Remote ON/OFF Connector

Remote ON/OFF Connector :
JST B-XH or equivalent

Open	Normal work
Short	Remote off


Relay dry contact Contact Rating :
1A @ 24VDC resistive



Bat. Low Alarm Connector

Bat. Low Alarm Connector :
JST B-XH or equivalent

Open	Battery low
Short	Battery OK



Type-B