



Test Report: SDR-75-12

75W Single Output Industrial DIN RAIL with Power Supply

■ DESIGN VERIFY TEST

Output Function Test

Input Function Test

Protection Function Test

Control Function Test

Component Stress Test

■ SAFETY & E.M.C. TEST

Safety Test

E.M.C. Test

■ RELIABILITY TEST

ENVIRONMENT TEST

DESIGN VERIFY TEST

OUTPUT FUNCTION TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	RIPPLE & NOISE	V1 : 100 mVp-p (Max)	I/P : 230VAC O/P : FULL LOAD Ta : 25°C	V1 : 16.8 mVp-p (Max)	P
2	OUTPUT VOLTAGE ADJUST RANGE	CH1 : 12V ~ 14 V	I/P : 230 VAC I/P : 115 VAC O/P : MIN LOAD Ta : 25°C	11.523 V ~ 14.611 V/ 230 VAC 11.522 V ~ 14.612 V/ 115 VAC	P
3	OUTPUT VOLTAGE TOLERANCE	V1 : 1 %~ -1 % (Max)	I/P : 100 VAC / 264 VAC O/P : FULL/ MIN LOAD Ta : 25°C	V1 : 0.21 %~ -0.21 %	P
4	LINE REGULATION	V1 : 0.5%~ -0.5% (Max)	I/P : 100 VAC ~ 264 VAC O/P : FULL LOAD Ta : 25°C	V1 : 0 %~ -0 %	P
5	LOAD REGULATION	V1 : 1%~ -1 % (Max)	I/P : 230 VAC O/P : FULL ~MIN LOAD Ta : 25°C	V1 : 0.21 %~ -0.21 %	P
6	SET UP TIME	230VAC : 1500 ms (Max) 115VAC : 3000 ms(Max)	I/P : 230 VAC I/P : 115 VAC O/P : FULL LOAD Ta : 25°C	230VAC/ 683 ms 115VAC/ 834 ms	P
7	RISE TIME	230VAC : 60 ms (Max) 115VAC : 60 ms (Max)	I/P : 230 VAC I/P : 115 VAC O/P : FULL LOAD Ta : 25°C	230VAC/ 6 ms 115VAC/ 6 ms	P
8	HOLD UP TIME	230VAC : 80 ms (TYP) 115VAC : 20 ms (TYP)	I/P : 230 VAC I/P : 115 VAC O/P : FULL LOAD Ta : 25°C	230VAC/ 105 ms 115VAC/ 22 ms	P
9	OVER/UNDERSHOOT TEST	< ±5%	I/P : 230 VAC O/P : FULL LOAD Ta : 25°C	TEST : <5 %	P
10	DYNAMIC LOAD	V1 : 1200 mVp-p	I/P : 230 VAC (1).O/P : FULL /Min LOAD 90%DUTY/ 1KHZ (2).O/P : FULL /Min LOAD 90%DUTY/ 3KHZ (3).O/P : FULL /Min LOAD 90%DUTY/ 5KHZ (4).O/P : FULL /Min LOAD 50%DUTY/ 120HZ Ta : 25°C	(1)292 mVp-p (2)282 mVp-p (3)278 mVp-p (4)302 mVp-p	P

INPUT FUNCTION TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	INPUT VOLTAGE RANGE	88 VAC~264 VAC	I/P : TESTING O/P : FULL LOAD Ta : 25°C I/P : LOW-LINE-3V=85 V HIGH-LINE+15%=300 V O/P : FULL/MIN LOAD ON : 30 Sec . OFF : 30 Sec 10MIN (AC POWER ON/OFF NO DAMAGE)	48.4V~264V TEST : OK	P
2	INPUT FREQUENCY RANGE	47HZ ~63 HZ NO DAMAGE OSC	I/P : 100 VAC ~ 264 VAC O/P : FULL~MIN LOAD Ta : 25°C	TEST : OK	P
3	EFFICIENCY	88.5 % (TYP)	I/P : 230 VAC O/P : FULL LOAD Ta : 25°C	89.3 %	P
4	INPUT CURRENT	230V/ 0.85 A (TYP) 115V/ 1.4 A (TYP)	I/P : 230 VAC I/P : 115 VAC O/P : FULL LOAD Ta : 25°C	I = 0.77 A/ 230 VAC I = 1.21 A/ 115 VAC	P
5	INRUSH CURRENT	230V/ 50 A (TYP) 115V/ 30 A(TYP) COLD START	I/P : 230 VAC I/P : 115 VAC O/P : FULL LOAD Ta : 25°C	I = 46 A/ 230 VAC I = 23 A/ 115 VAC	P
6	LEAKAGE CURRENT	< 1 mA / 240 VAC	I/P : 264 VAC O/P : Min LOAD Ta : 25°C	L-FG : 0.42 mA N-FG : 0.43 mA	p

PROTECTION FUNCTION TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	OVER LOAD PROTECTION	110% ~ 150 % 150% ~ 170 %	I/P : 230 VAC I/P : 115 VAC O/P : TESTING Ta : 25°C	120 %/ 230 VAC 120 %/ 115 VAC 158%/ 230 VAC 158%/ 115 VAC Normally works within 110 ~ 150% rated output power for more than 3 seconds and then shut down o/p voltage, re-power on to recover 150 ~ 170% rated power, constant current limiting with auto-recovery within 3 seconds, and than shut down o/p voltage after 3 seconds, re-power on to recover	P
2	OVER VOLTAGE PROTECTION	CH1 : 14V ~ 17 V	I/P : 230 VAC I/P : 115 VAC O/P : MIN LOAD Ta : 25°C	15.8 V/ 230 VAC 16 V/ 115 VAC Shut down Re- power ON	P
3	OVER TEMPERATURE PROTECTION	SPEC : RTH2 : 100 ± 10°C O.T.P. NO DAMAGE	I/P : 230 VAC O/P : FULL LOAD	O.T.P. Active Shut down o/p voltage , repower on to recovers after temperature goes down.	P

4	SHORT PROTECTION	SHORT EVERY OUTPUT 1 HOUR NO DAMAGE	I/P : 264 VAC O/P : FULL LOAD Ta : 25°C	NO DAMAGE constant current limiting with auto-recovery within 3 seconds, and than shut down o/p voltage after 3 seconds, re-power on to recover	P
---	------------------	--	---	--	---

COMPONENT STRESS TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	Power Transistor (D to S) or (C to E) Peak Voltage	Q1 Rated : STF13NM60N 11A/600V	I/P : High-Line +3V = 267 V O/P : (1)Full Load Turn on (2) Output Short (3)Full load continue Ta : 25°C	(1) 576 V (2) 476 V (3) 516 V	P
2	Diode Peak Voltage	Q100 Rated : IPP114N12N3 75A/120V	I/P : High-Line +3V = 267 V O/P : (1)Full Load Turn on (2)Output Short (3)Full load continue Ta : 25°C	(1) 89.2 V (2) 111 V (3) 79.2 V	P
3	Input Capacitor Voltage	C5 Rated: 180u/400V 105°C KMG	I/P : High-Line +3V = 267 V O/P : (1)Full Load Turn on /Off (2) Min load Turn on /Off (3)Full Load /Min load Change Ta : 25°C	(1) 388 V (2) 384 V (3) 382 V	P
4	Control IC Voltage Test	U1 Rated : NCP1380BDR2G: 9.4V~28V	I/P : High-Line +3V = 267 V O/P : (1)Full Load Turn on /Off (2) Min load Turn on /Off (3)Full Load /Min load Change Ta : 25°C	(1) 18.2 V (2) 17.3 V (3) 17.9 V	P

■ SAFETY & E.M.C. TEST

SAFETY TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	WITHSTAND VOLTAGE	I/P-O/P : 3 KVAC/min I/P-FG : 2 KVAC/min O/P-FG : 0.5 KVAC/min	I/P-O/P : 3.6 KVAC/min I/P-FG : 2.4 KVAC/min O/P-FG : 0.6 KVAC/min Ta : 25°C	I/P-O/P : 4.64 mA I/P-FG : 4.05 mA O/P-FG : 3.74 mA NO DAMAGE	P
2	ISOLATION RESISTANCE	I/P-O/P : 500VDC>100MΩ I/P-FG : 500VDC>100MΩ O/P-FG : 500VDC>100MΩ	I/P-O/P : 500 VDC I/P-FG : 500 VDC O/P-FG : 500 VDC Ta : 25°C /70%RH	I/P-O/P : 21.7 GΩ I/P-FG : 18.8 GΩ O/P-FG : 30 GΩ NO DAMAGE	P
3	GROUNDING CONTINUITY	FG(PE) TO CHASSIS OR TRACE < 100 mΩ	40 A / 2min Ta : 25°C / 70%RH	15 mΩ	P

E.M.C TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	HARMONIC	EN61000-3-2 CLASS A	I/P : 230 VAC/50HZ O/P : FULL LOAD Ta : 25°C	PASS	P
2	CONDUCTION	EN55022 CLASS B	I/P : 230 VAC (50HZ) O/P : FULL/50% LOAD Ta : 25°C	PASS Test by certified Lab	P
3	RADIATION	EN55022 CLASS B	I/P : 230 VAC (50HZ) O/P : FULL LOAD Ta : 25°C	PASS Test by certified Lab	P
4	E.S.D	EN61000-4-2 INDUSTRY AIR : 8KV / Contact : 4KV	I/P : 230 VAC/50HZ O/P : FULL LOAD Ta : 25°C	CRITERIA A	P
5	E.F.T	EN61000-4-4 INDUSTRY INPUT : 2KV	I/P : 230 VAC/50HZ O/P : FULL LOAD Ta : 25°C	CRITERIA A	P
6	SURGE	IEC61000-4-5 INDUSTRY L-N : 2KV L,N-PE : 4KV	I/P : 230 VAC/50HZ O/P : FULL LOAD Ta : 25°C	CRITERIA A	P
7	Test by certified Lab & Test Report Prepare				

RELIABILITY TEST

ENVIRONMENT TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT																																																																											
1	TEMPERATURE RISE TEST	MODEL : SDR-75-12 1. ROOM AMBIENT BURN-IN : 2 HRS I/P : 230VAC O/P : FULL LOAD Ta= 30.5 °C 2. HIGH AMBIENT BURN-IN : 16 HRS I/P : 230VAC O/P : FULL LOAD Ta= 52.9 °C <table><tr><th>NO</th><th>Position</th><th>PART NUMBER</th><th>ROOM AMBIENT Ta= 30.5 °C</th><th>HIGH AMBIENT Ta= 52.9 °C</th></tr><tr><td>1</td><td>BD1</td><td>6A/800V GLASS KBJ608G</td><td>61.7°C</td><td>81.5°C</td></tr><tr><td>2</td><td>C5</td><td>180u/400V 105°C 18*40 CLA IIR</td><td>54.4°C</td><td>75.6°C</td></tr><tr><td>3</td><td>T1</td><td>TF2532</td><td>71.5°C</td><td>93.2°C</td></tr><tr><td>4</td><td>Q100</td><td>IPP114N12N3 75A/120V TO220</td><td>77.0°C</td><td>99.4°C</td></tr><tr><td>5</td><td>C105</td><td>1000u/16V UL10Kh 10*16 ZLH</td><td>69.1°C</td><td>90.6°C</td></tr><tr><td>6</td><td>LF100</td><td>TR891-R4</td><td>56.2°C</td><td>78.3°C</td></tr><tr><td>7</td><td>U1</td><td>NCP1380BDR2G SO-8</td><td>53.0°C</td><td>74.7°C</td></tr><tr><td>8</td><td>Q1</td><td>STF13NM60N 11A/600V TO220FP</td><td>55.7°C</td><td>78.2°C</td></tr><tr><td>9</td><td>C38</td><td>10u/50V UL10Kh 5*11 LE</td><td>53.7°C</td><td>75.3°C</td></tr><tr><td>10</td><td>C36</td><td>47u/50V UL10Kh 6.3*11 LE</td><td>61.7°C</td><td>83.5°C</td></tr><tr><td>11</td><td>C200</td><td>100u/50V UL9Kh 8*11.5 ZLJ</td><td>58.4°C</td><td>80.2°C</td></tr><tr><td>12</td><td>C205</td><td>47u/25V UL10Kh 5*11 LE</td><td>61.4°C</td><td>83.4°C</td></tr><tr><td>13</td><td>RTH2</td><td>100KΩ 3Φ TTC3A104F4193EY 1%</td><td>60.3°C</td><td>82.2°C</td></tr><tr><td>14</td><td>C186</td><td>330u/25V UL8Kh 8*11.5 ZLH</td><td>55.6°C</td><td>77.5°C</td></tr></table>			NO	Position	PART NUMBER	ROOM AMBIENT Ta= 30.5 °C	HIGH AMBIENT Ta= 52.9 °C	1	BD1	6A/800V GLASS KBJ608G	61.7°C	81.5°C	2	C5	180u/400V 105°C 18*40 CLA IIR	54.4°C	75.6°C	3	T1	TF2532	71.5°C	93.2°C	4	Q100	IPP114N12N3 75A/120V TO220	77.0°C	99.4°C	5	C105	1000u/16V UL10Kh 10*16 ZLH	69.1°C	90.6°C	6	LF100	TR891-R4	56.2°C	78.3°C	7	U1	NCP1380BDR2G SO-8	53.0°C	74.7°C	8	Q1	STF13NM60N 11A/600V TO220FP	55.7°C	78.2°C	9	C38	10u/50V UL10Kh 5*11 LE	53.7°C	75.3°C	10	C36	47u/50V UL10Kh 6.3*11 LE	61.7°C	83.5°C	11	C200	100u/50V UL9Kh 8*11.5 ZLJ	58.4°C	80.2°C	12	C205	47u/25V UL10Kh 5*11 LE	61.4°C	83.4°C	13	RTH2	100KΩ 3Φ TTC3A104F4193EY 1%	60.3°C	82.2°C	14	C186	330u/25V UL8Kh 8*11.5 ZLH	55.6°C	77.5°C	P
NO	Position	PART NUMBER	ROOM AMBIENT Ta= 30.5 °C	HIGH AMBIENT Ta= 52.9 °C																																																																												
1	BD1	6A/800V GLASS KBJ608G	61.7°C	81.5°C																																																																												
2	C5	180u/400V 105°C 18*40 CLA IIR	54.4°C	75.6°C																																																																												
3	T1	TF2532	71.5°C	93.2°C																																																																												
4	Q100	IPP114N12N3 75A/120V TO220	77.0°C	99.4°C																																																																												
5	C105	1000u/16V UL10Kh 10*16 ZLH	69.1°C	90.6°C																																																																												
6	LF100	TR891-R4	56.2°C	78.3°C																																																																												
7	U1	NCP1380BDR2G SO-8	53.0°C	74.7°C																																																																												
8	Q1	STF13NM60N 11A/600V TO220FP	55.7°C	78.2°C																																																																												
9	C38	10u/50V UL10Kh 5*11 LE	53.7°C	75.3°C																																																																												
10	C36	47u/50V UL10Kh 6.3*11 LE	61.7°C	83.5°C																																																																												
11	C200	100u/50V UL9Kh 8*11.5 ZLJ	58.4°C	80.2°C																																																																												
12	C205	47u/25V UL10Kh 5*11 LE	61.4°C	83.4°C																																																																												
13	RTH2	100KΩ 3Φ TTC3A104F4193EY 1%	60.3°C	82.2°C																																																																												
14	C186	330u/25V UL8Kh 8*11.5 ZLH	55.6°C	77.5°C																																																																												
2	OVER LOAD BURN-IN TEST	NO DAMAGE 1 HOUR (MIN)	I/P : 230 VAC O/P : 120 % LOAD Ta : 25°C	TEST : OK	P																																																																											
3	LOW TEMPERATURE TURN ON TEST	TURN ON AFTER 2 HOUR	I/P : 264VAC/100VAC O/P : 100 % LOAD Ta= -35°C / -30°C	TEST : OK	P																																																																											
4	HIGH HUMIDITY HIGH TEMPERATURE HIGH VOLTAGE TURN ON TEST	AFTER 12 HOURS IN CHAMBER ON CONTROL 55 °C NO DAMAGE	I/P : 272 VAC O/P : FULL LOAD Ta= 55 °C HUMIDITY= 95 %R.H	TEST : OK	P																																																																											
5	TEMPERATURE COEFFICIENT	± 0.03 %/°C (0~50°C)	I/P : 230 VAC O/P : FULL LOAD	± 0.008 %/°C (0~50°C)	P																																																																											
6	STORAGE TEMPERATURE TEST	1. Thermal shock Temperature : -45°C~ +90°C 2. Temperature change rate : 25°C / MIN 3. Dwell time low and high temperature : 30 MIN/EACH 4. Total test cycle : 5 CYCLE 5. Input/Output condition : STATIC		OK	P																																																																											

7	THERMAL SHOCK TEST	1. Thermal shock Temperature : -35℃~ +60℃ 2. Temperature change rate : 25℃ / MIN 3. Dwell time low and high temperature : 30 MIN/EACH 4. Total test cycle : 10 CYCLE 5. Input/Output condition : 230VAC/Full Load AC ON/OFF TEST turn on 58sec ; turn off 2sec	OK	P
8	VIBRATION TEST	1 Carton & 1 Set (1) Waveform : Sine Wave (2) Frequency : 10~500Hz (3) Sweep Time : 12min/sweep cycle (4) Acceleration : 2G (5) Test Time : 60min in each axis (X.Y.Z) (6) Ta : 25℃	TEST : OK	P
9	CAPACITOR LIFE CYCLE	SUPPOSE C105 IS THE MOST CRITICAL COMPONENT (1) I/P : 230VAC O/P : FULL LOAD Ta= 25 °C LIFE TIME (2) I/P : 230VAC O/P : FULL LOAD Ta= 55 °C LIFE TIME (3) I/P : 230VAC O/P : 75% LOAD Ta= 55 °C LIFE TIME (4) I/P : 230VAC O/P : 50% LOAD Ta= 55 °C LIFE TIME	(1) 216672 HRS (2) 28881HRS (3) 54936HRS (4) 90454HRS	P
10	MTBF	MIL-HDBK-217F NOTICE S2 PARTS COUNT TOTAL FAILURE RATE : 481.9 KHRS		P
11	DMTBF/Accelerated Life Test	Demonstration Mean Time Between Failure (Expected Life): Above 30,000 hours @ TA 55℃		P

DATE	SAMPLE	TESTER	REVIEW	APPROVAL
2013/4/2	RD SAMPLE	DANIEL GAO	SANFORD SU	VINCENT TSENG
2013/4/24	PRODUCT SAMPLE	DANIEL GAO	SANFORD SU	VINCENT TSENG

12.10.30 A50-F031