



Test Report: HRP-100-15

100W Single Output with PFC Function

■ DESIGN VERIFY TEST

Output Function Test

Input Function Test

Protection Function Test

Control Function Test

Component Stress Test

■ SAFETY & E.M.C. TEST

Safety Test

E.M.C. Test

■ RELIABILITY TEST

ENVIRONMENT TEST

DESIGN VERIFY TEST

OUTPUT FUNCTION TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	RIPPLE & NOISE	V1 : 150 mVp-p (Max)	I/P : 230VAC O/P : FULL LOAD Ta : 25°C	V1 : 104 mVp-p (Max)	P
2	OUTPUT VOLTAGE ADJUST RANGE	CH1 : 14.25V ~ 18 V	I/P : 230 VAC I/P : 115 VAC O/P : MIN LOAD Ta : 25°C	13.074 V ~ 18.541 V/ 230 VAC 13.075 V ~ 18.541 V/ 115 VAC	P
3	OUTPUT VOLTAGE TOLERANCE	V1 : 1.5 %~ -1.5 % (Max)	I/P : 100 VAC / 264 VAC O/P : FULL/ MIN LOAD Ta : 25°C	V1 : 0.45 %~ -0.45 %	P
4	LINE REGULATION	V1 : 0.3 %~ -0.3 % (Max)	I/P : VAC ~ 264 VAC O/P : FULL LOAD Ta : 25°C	V1 : 0 %~ 0 %	P
5	LOAD REGULATION	V1 : 0.8 %~ -0.8 % (Max)	I/P : 230 VAC O/P : FULL ~MIN LOAD Ta : 25°C	V1 : 0.42 %~ 0.42 %	P
6	SET UP TIME	230VAC : 2500 ms (Max) 115VAC : 2500 ms(Max)	I/P : 230 VAC I/P : 115 VAC O/P : FULL LOAD Ta : 25°C	230VAC/ 911 ms 115VAC/ 1822 ms	P
7	RISE TIME	230VAC : 50 ms (Max) 115VAC : 50 ms (Max)	I/P : 230 VAC I/P : 115 VAC O/P : FULL LOAD Ta : 25°C	230VAC/ 10 ms 115VAC/ 10 ms	P
8	HOLD UP TIME	230VAC : 50 ms (TYP) 115VAC : 20 ms (TYP)	I/P : 230 VAC I/P : 115 VAC O/P : FULL LOAD Ta : 25°C	230VAC/ 59 ms 115VAC/ 22 ms	P
9	OVER/UNDERSHOOT TEST	< ±5%	I/P : 230 VAC O/P : FULL LOAD Ta : 25°C	TEST : < 5 %	P
10	DYNAMIC LOAD	V1 : 1500 mVp-p	I/P : 230 VAC O/P : FULL /Min LOAD 90%DUTY/ 1KHZ Ta : 25°C	306 mVp-p	P

INPUT FUNCTION TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	INPUT VOLTAGE RANGE	85VAC~264 VAC	I/P : TESTING O/P : FULL LOAD Ta : 25°C	80 V~264V	P
			I/P : LOW-LINE-3V= 82 V HIGH-LINE+15%=300 V O/P : FULL/MIN LOAD ON : 30 Sec. OFF : 30 Sec 10MIN (AC POWER ON/OFF NO DAMAGE)	TEST : OK	
2	INPUT FREQUENCY RANGE	47HZ ~63 HZ NO DAMAGE OSC	I/P : 85 VAC ~ 264 VAC O/P : FULL~MIN LOAD Ta : 25°C	TEST : OK	P
3	POWER FACTOR	0.95 / 230 VAC(TYP) 0.98 / 115 VAC(TYP)	I/P : 230 VAC I/P : 115 VAC O/P : FULL LOAD Ta : 25°C	PF= 0.97 / 230 VAC PF= 1 / 115 VAC	P
4	EFFICIENCY	88 % (TYP)	I/P : 230 VAC O/P : FULL LOAD Ta : 25°C	88.58 %	P
5	INPUT CURRENT	230V/ 0.6 A (TYP) 115V/ 1.2 A (TYP)	I/P : 230 VAC I/P : 115 VAC O/P : FULL LOAD Ta : 25°C	I = 0.52 A/ 230 VAC I = 1.05 A/ 115 VAC	P
6	INRUSH CURRENT	230V/ 65 A (TYP) 115V/ 35 A(TYP) COLD START	I/P : 230 VAC I/P : 115 VAC O/P : FULL LOAD Ta : 25°C	I = 32 A/ 230 VAC I = 16 A/ 115 VAC	P
7	LEAKAGE CURRENT	< 1 mA / 240 VAC	I/P : 264 VAC O/P : Min LOAD Ta : 25°C	L-FG : 0.31 mA N-FG : 0.28 mA	P
8	NO LOAD POWER CONSUMPTION	<0.454W	I/P : 240 VAC O/P : NO LOAD Ta : 25°C	0.35W	P

PROTECTION FUNCTION TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	OVER LOAD PROTECTION	105 %~ 135 %	I/P : 230 VAC I/P : 115 VAC O/P : TESTING Ta : 25°C	129 %/ 230 VAC 129 %/ 115 VAC Constant current limiting for Vo=50 ~ 100% of rated voltage, recovers automatically after fault condition is removed	P
2	OVER VOLTAGE PROTECTION	CH1 : 18.8 V~ 21.8V	I/P : 230 VAC I/P : 115 VAC O/P : MIN LOAD Ta : 25°C	19.77 V/ 230 VAC 19.77 V/ 115 VAC Shut down Re- power ON	P
3	OVER TEMPERATURE PROTECTION (optional)	SPEC : TSW1 : $85 \pm 5^{\circ}\text{C}$ O.T.P. TSW1 : detect on heatsink Q101 of power transistor NO DAMAGE	I/P : 230 VAC O/P : FULL LOAD	O.T.P. Active Shut down o/p voltage , recovers automatically after temperature goes down	P
4	SHORT PROTECTION	SHORT EVERY OUTPUT 1 HOUR NO DAMAGE	I/P : 264 VAC O/P : FULL LOAD Ta : 25°C	NO DAMAGE Hiccup Mode	P

CONTROL FUNCTION TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	REMOTE CONTROL	Rc+ / Rc- 0 V~ 0.8 V POWER ON 4 V~ 10V POWER OFF	I/P : 230 VAC O/P : FULL LOAD Ta : 25°C	0 V~1.7 V POWER ON 1.8 V~10 V POWER OFF	P

COMPONENT STRESS TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	Power Transistor (D to S) or (C to E) Peak Voltage	Q 3 Rated : 2SK3673-01MR 10A/700V	I/P : High-Line +3V = 267 V O/P : (1)Full Load Turn on (2) Output Short (3)Full load continue Ta : 25°C	(1) 676 V (2) 552 V (3) 650 V	P
2	Diode Peak Voltage	Q101 Rated : STP80N10 80A/100V Q102 Rated : STP80N10 80A/100V	I/P : High-Line +3V = 267 V O/P : (1)Full Load Turn on (2)Output Short (3)Full load continue Ta : 25°C	(1) 99 V (2) 93.6 V (3) 70.8 V (1) 99 V (2) 93 V (3) 70 V	P
3	Clamp Diode Peak Voltage	D2 Rated : 3A/600V 1N5406	I/P : High-Line +3V = 267 V O/P : (1) Dynamic Load 90%Duty/1KHz (2)Full load continue Ta : 25°C	(1) 544 V (2) 552 V	P
4	Input Capacitor Voltage	C5 Rated : 100u/400V 105°C	I/P : High-Line +3V = 267 V O/P : (1)Full Load Turn on /Off (2) Min load Turn on /Off (3)Full Load /Min load Change Ta : 25°C	(1) 380 V (2) 377 V (3) 399 V	P
5	Control IC Voltage Test	U1 Rated : PFC FAN6921MR 30V(max) 7.8V(min) U101 Rated : TEA1761T 38V(max) 8.35V(min)	I/P : High-Line +3V = 267 V O/P : (1)Full Load Turn on /Off (2) Min load Turn on /Off (3)Full Load /Min load Change Ta : 25°C	(1) 22.81 V (2) 17.8 V (3) 23.1 V (1) 18.27 V (2) 12.85 V (3) 18.27 V	P
6	Power Transistor (D to S) or (C to E) Peak Voltage	Q1 Rated : 2SK4106 12A/500V	I/P : High-Line +3V = 267 V O/P : (1)Full Load Turn on (2) Output Short (3)Full load continue Ta : 25°C	(1) 460 V (2) 408 V (3) 440 V	P

■ SAFETY & E.M.C. TEST

SAFETY TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	WITHSTAND VOLTAGE	I/P-O/P : 3 KVAC/min I/P-FG : 2 KVAC/min O/P-FG : 0.5 KVAC/min	I/P-O/P : 3.6 KVAC/min I/P-FG : 2.4 KVAC/min O/P-FG : 0.6 KVAC/min Ta : 25°C	I/P-O/P : 3.77 mA I/P-FG : 2.851 mA O/P-FG : 2.035 mA NO DAMAGE	P
2	ISOLATION RESISTANCE	I/P-O/P : 500VDC>100MΩ I/P-FG : 500VDC>100MΩ O/P-FG : 500VDC>100MΩ	I/P-O/P : 500 VDC I/P-FG : 500 VDC O/P-FG : 500 VDC Ta : 25°C /70%RH	I/P-O/P : 30 GΩ I/P-FG : 30 GΩ O/P-FG : 30 GΩ NO DAMAGE	P
3	GROUNDING CONTINUITY	FG(PE) TO CHASSIS OR TRACE < 100 mΩ	40 A / 2min Ta : 25°C / 70%RH	12 mΩ	P
4	APPROVAL	TUV : Certificate NO : R50171849 UL : File NO : E183223			P

E.M.C TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	HARMONIC	EN61000-3-2,-3 CLASS A	I/P : 230 VAC/50HZ O/P : FULL LOAD Ta : 25°C	PASS	P
2	CONDUCTION	EN55022 CLASS B	I/P : 230 VAC (50HZ) O/P : FULL/50% LOAD Ta : 25°C	PASS Test by certified Lab	P
3	RADIATION	EN55022 CLASS B	I/P : 230 VAC (50HZ) O/P : FULL LOAD Ta : 25°C	PASS Test by certified Lab	P
4	E.S.D	EN61000-4-2 INDUSTRY AIR : 8KV / Contact : 4KV	I/P : 230 VAC/50HZ O/P : FULL LOAD Ta : 25°C	CRITERIA A	P
5	E.F.T	EN61000-4-4 INDUSTRY INPUT : 2KV	I/P : 230 VAC/50HZ O/P : FULL LOAD Ta : 25°C	CRITERIA A	P
6	SURGE	IEC61000-4-5 INDUSTRY L-N : 2KV L,N-PE : 4KV	I/P : 230 VAC/50HZ O/P : FULL LOAD Ta : 25°C	CRITERIA A	P
7	Test by certified Lab & Test Report Prepare				

RELIABILITY TEST

ENVIRONMENT TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT																																																																																																									
1.	THERMO TRACER TEST (ROOM AMBIENT)	MODEL:HRP-100-5 95020002.LRI (点検温度) 116 107 97 88 78 69 59 50 40 30 21 1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 116.3℃ 25.1℃(EO.94) 25.1℃(EO.94) 20.0℃ 85.9℃ 228.109 23.0℃ 0 0.940 2009/ 5/ 2 10:15:49 p 1: 57.2℃ 59x, 60y p 2: 38.8℃ 118x, 55y p 3: 39.4℃ 136x, 55y p 4: 45.7℃ 176x, 45y p 5: 44.1℃ 285x, 51y p 6: 42.9℃ 302x, 72y p 7: 45.0℃ 304x, 102y p 8: 49.2℃ 285x, 105y p 9: 75.1℃ 195x, 137y p10: 66.3℃ 221x, 129y p11: 75.6℃ 216x, 188y p12: 67.5℃ 137x, 166y p13: 66.2℃ 107x, 104y p14: 60.7℃ 62x, 147y p15: 55.9℃ 121x, 191y <table><thead><tr><th></th><th>Position</th><th>Temp</th><th>VERDICT</th></tr></thead><tbody><tr><td>P1</td><td>Rth1</td><td>57.2℃</td><td>PASS</td></tr><tr><td>P2</td><td>LF1</td><td>38.8℃</td><td>PASS</td></tr><tr><td>P3</td><td>LF2</td><td>39.4℃</td><td>PASS</td></tr><tr><td>P4</td><td>BD</td><td>45.7℃</td><td>PASS</td></tr><tr><td>P5</td><td>L3-CORE</td><td>44.1℃</td><td>PASS</td></tr><tr><td>P6</td><td>D1</td><td>42.9℃</td><td>PASS</td></tr><tr><td>P7</td><td>Q1</td><td>45℃</td><td>PASS</td></tr><tr><td>P8</td><td>C5</td><td>49.2℃</td><td>PASS</td></tr><tr><td>P9</td><td>T1-COIL</td><td>75.1℃</td><td>PASS</td></tr><tr><td>P10</td><td>D2</td><td>66.3℃</td><td>PASS</td></tr><tr><td>P11</td><td>Cap-Vcc</td><td>75.6℃</td><td>PASS</td></tr><tr><td>P12</td><td>Q101</td><td>67.5℃</td><td>PASS</td></tr><tr><td>P13</td><td>C105</td><td>66.2℃</td><td>PASS</td></tr><tr><td>P14</td><td>L100</td><td>60.7℃</td><td>PASS</td></tr><tr><td>P15</td><td>Cap-Vb</td><td>55.9℃</td><td>PASS</td></tr></tbody></table>				Position	Temp	VERDICT	P1	Rth1	57.2℃	PASS	P2	LF1	38.8℃	PASS	P3	LF2	39.4℃	PASS	P4	BD	45.7℃	PASS	P5	L3-CORE	44.1℃	PASS	P6	D1	42.9℃	PASS	P7	Q1	45℃	PASS	P8	C5	49.2℃	PASS	P9	T1-COIL	75.1℃	PASS	P10	D2	66.3℃	PASS	P11	Cap-Vcc	75.6℃	PASS	P12	Q101	67.5℃	PASS	P13	C105	66.2℃	PASS	P14	L100	60.7℃	PASS	P15	Cap-Vb	55.9℃	PASS	P																																									
	Position	Temp	VERDICT																																																																																																											
P1	Rth1	57.2℃	PASS																																																																																																											
P2	LF1	38.8℃	PASS																																																																																																											
P3	LF2	39.4℃	PASS																																																																																																											
P4	BD	45.7℃	PASS																																																																																																											
P5	L3-CORE	44.1℃	PASS																																																																																																											
P6	D1	42.9℃	PASS																																																																																																											
P7	Q1	45℃	PASS																																																																																																											
P8	C5	49.2℃	PASS																																																																																																											
P9	T1-COIL	75.1℃	PASS																																																																																																											
P10	D2	66.3℃	PASS																																																																																																											
P11	Cap-Vcc	75.6℃	PASS																																																																																																											
P12	Q101	67.5℃	PASS																																																																																																											
P13	C105	66.2℃	PASS																																																																																																											
P14	L100	60.7℃	PASS																																																																																																											
P15	Cap-Vb	55.9℃	PASS																																																																																																											
2	TEMPERATURE RISE TEST	MODEL : HRP-100-5 1. ROOM AMBIENT BURN-IN : 3 HRS I/P : 230VAC O/P : FULL LOAD Ta= 27.1 °C 2. HIGH AMBIENT BURN-IN : 5 HRS I/P : 230VAC O/P : FULL LOAD Ta= 43.1 °C <table><thead><tr><th>NO</th><th>Position</th><th>P/N</th><th>ROOM AMBIENT Ta= 27.1 °C</th><th>HIGH AMBIENT Ta= 43.1 °C</th></tr></thead><tbody><tr><td>1</td><td>D2</td><td>3A/600V 1N5406 DO-201</td><td>97.8℃</td><td>112.1℃</td></tr><tr><td>2</td><td>D30</td><td>1A/1KV 1N4007</td><td>102.4℃</td><td>119.1℃</td></tr><tr><td>3</td><td>D150</td><td>1A/1KV 1N4007</td><td>84.5℃</td><td>99.3℃</td></tr><tr><td>4</td><td>LF2</td><td>TR653-R2</td><td>52.2℃</td><td>68.4℃</td></tr><tr><td>5</td><td>BD1</td><td>6A/800V US6KB80R-7000</td><td>60.2℃</td><td>76.0℃</td></tr><tr><td>6</td><td>L1</td><td>TR654-R4</td><td>51.0℃</td><td>66.7℃</td></tr><tr><td>7</td><td>L3</td><td>TF1965</td><td>54.8℃</td><td>69.7℃</td></tr><tr><td>8</td><td>C11</td><td>474/450V 10% P=10 MMX</td><td>57.5℃</td><td>73.1℃</td></tr><tr><td>9</td><td>D1</td><td>BYV29X-600 7A/600V</td><td>50.9℃</td><td>67.2℃</td></tr><tr><td>10</td><td>Q1</td><td>2SK4106 12A/500V</td><td>54.7℃</td><td>71.2℃</td></tr><tr><td>11</td><td>Q3</td><td>2SK3673-01MR 10A/700V</td><td>62.2℃</td><td>79.3℃</td></tr><tr><td>12</td><td>C5</td><td>100u/400V 105℃ 18*25 KMG</td><td>70.4℃</td><td>85.9℃</td></tr><tr><td>13</td><td>T1</td><td>TF1958</td><td>85.5℃</td><td>102.8℃</td></tr><tr><td>14</td><td>C18</td><td>47u/50V 6.3*11 YXF</td><td>83.0℃</td><td>100.1℃</td></tr><tr><td>15</td><td>C61</td><td>47u/50V 6.3*11 KY</td><td>67.4℃</td><td>83.4℃</td></tr><tr><td>16</td><td>C150</td><td>47u/50V 6.3*11 YXF</td><td>74.9℃</td><td>90.6℃</td></tr><tr><td>17</td><td>C105</td><td>3900u/10V UL10Kh 12.5*25 ZLH</td><td>71.7℃</td><td>88.8℃</td></tr><tr><td>18</td><td>C108</td><td>3900u/10V UL10Kh 12.5*25 ZLH</td><td>71.3℃</td><td>88.3℃</td></tr><tr><td>19</td><td>Q101</td><td>IRF1405Z 75A/55V</td><td>75.2℃</td><td>92.8℃</td></tr><tr><td>20</td><td>TSW1</td><td>ST-22W-R3 90℃ 130mm</td><td>63.6℃</td><td>80.4℃</td></tr></tbody></table>			NO	Position	P/N	ROOM AMBIENT Ta= 27.1 °C	HIGH AMBIENT Ta= 43.1 °C	1	D2	3A/600V 1N5406 DO-201	97.8℃	112.1℃	2	D30	1A/1KV 1N4007	102.4℃	119.1℃	3	D150	1A/1KV 1N4007	84.5℃	99.3℃	4	LF2	TR653-R2	52.2℃	68.4℃	5	BD1	6A/800V US6KB80R-7000	60.2℃	76.0℃	6	L1	TR654-R4	51.0℃	66.7℃	7	L3	TF1965	54.8℃	69.7℃	8	C11	474/450V 10% P=10 MMX	57.5℃	73.1℃	9	D1	BYV29X-600 7A/600V	50.9℃	67.2℃	10	Q1	2SK4106 12A/500V	54.7℃	71.2℃	11	Q3	2SK3673-01MR 10A/700V	62.2℃	79.3℃	12	C5	100u/400V 105℃ 18*25 KMG	70.4℃	85.9℃	13	T1	TF1958	85.5℃	102.8℃	14	C18	47u/50V 6.3*11 YXF	83.0℃	100.1℃	15	C61	47u/50V 6.3*11 KY	67.4℃	83.4℃	16	C150	47u/50V 6.3*11 YXF	74.9℃	90.6℃	17	C105	3900u/10V UL10Kh 12.5*25 ZLH	71.7℃	88.8℃	18	C108	3900u/10V UL10Kh 12.5*25 ZLH	71.3℃	88.3℃	19	Q101	IRF1405Z 75A/55V	75.2℃	92.8℃	20	TSW1	ST-22W-R3 90℃ 130mm	63.6℃	80.4℃	P
NO	Position	P/N	ROOM AMBIENT Ta= 27.1 °C	HIGH AMBIENT Ta= 43.1 °C																																																																																																										
1	D2	3A/600V 1N5406 DO-201	97.8℃	112.1℃																																																																																																										
2	D30	1A/1KV 1N4007	102.4℃	119.1℃																																																																																																										
3	D150	1A/1KV 1N4007	84.5℃	99.3℃																																																																																																										
4	LF2	TR653-R2	52.2℃	68.4℃																																																																																																										
5	BD1	6A/800V US6KB80R-7000	60.2℃	76.0℃																																																																																																										
6	L1	TR654-R4	51.0℃	66.7℃																																																																																																										
7	L3	TF1965	54.8℃	69.7℃																																																																																																										
8	C11	474/450V 10% P=10 MMX	57.5℃	73.1℃																																																																																																										
9	D1	BYV29X-600 7A/600V	50.9℃	67.2℃																																																																																																										
10	Q1	2SK4106 12A/500V	54.7℃	71.2℃																																																																																																										
11	Q3	2SK3673-01MR 10A/700V	62.2℃	79.3℃																																																																																																										
12	C5	100u/400V 105℃ 18*25 KMG	70.4℃	85.9℃																																																																																																										
13	T1	TF1958	85.5℃	102.8℃																																																																																																										
14	C18	47u/50V 6.3*11 YXF	83.0℃	100.1℃																																																																																																										
15	C61	47u/50V 6.3*11 KY	67.4℃	83.4℃																																																																																																										
16	C150	47u/50V 6.3*11 YXF	74.9℃	90.6℃																																																																																																										
17	C105	3900u/10V UL10Kh 12.5*25 ZLH	71.7℃	88.8℃																																																																																																										
18	C108	3900u/10V UL10Kh 12.5*25 ZLH	71.3℃	88.3℃																																																																																																										
19	Q101	IRF1405Z 75A/55V	75.2℃	92.8℃																																																																																																										
20	TSW1	ST-22W-R3 90℃ 130mm	63.6℃	80.4℃																																																																																																										
3	OVER LOAD BURN-IN TEST	NO DAMAGE 1 HOUR (MIN)	I/P : 230 VAC O/P : 123 % LOAD Ta : 25℃	TEST : OK	P																																																																																																									

4	LOW TEMPERATURE TURN ON TEST	TURN ON AFTER 2 HOUR	I/P : 264VAC/100VAC O/P : 100 % LOAD Ta= -40 °C	TEST : OK	P
5	HIGH HUMIDITY HIGH TEMPERATURE HIGH VOLTAGE TURN ON TEST	AFTER 12 HOURS IN CHAMBER ON CONTROL 40 °C NO DAMAGE	I/P : 272 VAC O/P : FULL LOAD Ta= 40°C HUMIDITY= 95 %R.H	TEST : OK	P
6	TEMPERATURE COEFFICIENT	± 0.04 %(0~50°C)	I/P : 230 VAC O/P : FULL LOAD	± 0 %(0~50°C)	P
7	STORAGE TEMPERATURE TEST	1. Thermal shock Temperature : -45°C ~ +90°C 2. Temperature change rate : 25°C / MIN 3. Dwell time low and high temperature : 30 MIN/EACH 4. Total test cycle : 5 CYCLE 5. Input/Output condition : STATIC		OK	P
8.	THERMAL SHOCK TEST	1. Thermal shock Temperature : -40°C ~ +45°C 2. Temperature change rate : 25°C / MIN 3. Dwell time low and high temperature : 30 MIN/EACH 4. Total test cycle : 10 CYCLE 5. Input/Output condition : 230VAC/Full Load		OK	P
9	VIBRATION TEST	1 Carton & 1 Set (1) Waveform : Sine Wave (2) Frequency : 10~500Hz (3) Sweep Time : 12min/sweep cycle (4) Acceleration : 5G (5) Test Time : 60min in each axis (X.Y.Z) (6) Ta : 25°C		TEST : OK	P
10	CAPACITOR LIFE CYCLE	HRP-100-5: SUPPOSE C 105 IS THE MOST CRITICAL COMPONENT (1) I/P : 230VAC O/P : FULL LOAD Ta= 25 °C LIFE TIME (2) I/P : 230VAC O/P : FULL LOAD Ta= 40 °C LIFE TIME (3) I/P : 230VAC O/P : 75% LOAD Ta= 40 °C LIFE TIME		(1) 142932.7HRS (2) 46824.9HRS (3) 102498.6HRS	P
11	MTBF	MIL-HDBK-217F NOTICES2 PARTS COUNT TOTAL FAILURE RATE : 295.7K HRS			P

DATE	SAMPLE	TEST RESULT	TESTER	APPROVAL
2009/11/4	RD SAMPLE	PASS	SANFORD SU	VINCENT TSENG
2009/11/27	RD SAMPLE(2)	PASS	SANFORD SU	VINCENT TSENG
2010/1/15	PRODUCT SAMPLE W0912D11	PASS	SANFORD SU	VINCENT TSENG

2003/12/12 A50-F023