



Test Report: RSP-200-48

200W Single Output With PFC Function

■ DESIGN VERIFY TEST

Output Function Test

Input Function Test

Protection Function Test

Component Stress Test

■ SAFETY & E.M.C. TEST

Safety Test

E.M.C. Test

■ RELIABILITY TEST

ENVIRONMENT TEST

DESIGN VERIFY TEST

OUTPUT FUNCTION TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	RIPPLE & NOISE	V1 : 150 mVp-p (Max)	I/P : 230VAC O/P : FULL LOAD Ta : 25°C	V1 : 22.8 mVp-p (Max)	P
2	OUTPUT VOLTAGE ADJUST RANGE	CH1 : 41V ~ 56V	I/P : 230 VAC I/P : 115 VAC O/P : MIN LOAD Ta : 25°C	38.114 V ~ 58.03 V/ 230 VAC 38.128 V ~ 58.03 V/ 115 VAC	P
3	OUTPUT VOLTAGE TOLERANCE	V1 : 1 %~ -1% (Max)	I/P : 100VAC / 264 VAC O/P : FULL/ MIN LOAD Ta : 25°C	V1 : 0.02 %~ -0.02 %	P
4	LINE REGULATION	V1 : 0.2%~ -0.2 % (Max)	I/P : 100 VAC ~ 264 VAC O/P : FULL LOAD Ta : 25°C	V1 : 0 %~ 0 %	P
5	LOAD REGULATION	V1 : 0.5 %~ -0.5 % (Max)	I/P : 230 VAC O/P : FULL ~MIN LOAD Ta : 25°C	V1 : 0.02 %~ -0.02 %	P
6	SET UP TIME	230VAC : 1500 ms (Max) 115VAC : 3000 ms(Max)	I/P : 230 VAC I/P : 115 VAC O/P : FULL LOAD Ta : 25°C	230VAC/ 464 ms 115VAC/ 928 ms	P
7	RISE TIME	230VAC : 50 ms (Max) 115VAC : 50 ms (Max)	I/P : 230 VAC I/P : 115 VAC O/P : FULL LOAD Ta : 25°C	230VAC/ 20 ms 115VAC/ 21 ms	P
8	HOLD UP TIME	230VAC : 8 ms (TYP) 115VAC : 8 ms (TYP)	I/P : 230 VAC I/P : 115 VAC O/P : FULL LOAD Ta : 25°C	230VAC/ 21 ms 115VAC/ 17 ms	P
9	OVER/UNDERSHOOT TEST	< ±5%	I/P : 230 VAC O/P : FULL LOAD Ta : 25°C	TEST : <5 %	P
10	DYNAMIC LOAD	V1 : 4800 mVp-p	I/P : 230 VAC (1).O/P : FULL /Min LOAD 90%DUTY/ 1KHZ (2).O/P : FULL /Min LOAD 90%DUTY/ 3KHZ (3).O/P : FULL /Min LOAD 90%DUTY/ 5KHZ (4).O/P : FULL /Min LOAD 50%DUTY/ 120HZ Ta : 25°C	(1) 484 mVp-p (2) 248 mVp-p (3) 264 mVp-p (4) 524 mVp-p	P

INPUT FUNCTION TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	INPUT VOLTAGE RANGE	100VAC~264 VAC	I/P : TESTING O/P : FULL LOAD Ta : 25°C	69 V~264V	P
			I/P : LOW-LINE-3V= 97 V HIGH-LINE+15%=300 V O/P : FULL/MIN LOAD ON : 30 Sec . OFF : 30 Sec 10MIN (AC POWER ON/OFF NO DAMAGE)	TEST : OK	
2	INPUT FREQUENCY RANGE	47HZ ~63 HZ NO DAMAGE OSC	I/P : 100 VAC ~ 264 VAC O/P : FULL~MIN LOAD Ta : 25°C	TEST : OK	P
3	POWER FACTOR	0.95 / 230 VAC(TYP) 0.98 / 115 VAC(TYP)	I/P : 230 VAC I/P : 115 VAC O/P : FULL LOAD Ta : 25°C	PF= 0.972 / 230 VAC PF= 0.997 / 115 VAC	P
4	EFFICIENCY	90% (TYP)	I/P : 230 VAC O/P : FULL LOAD Ta : 25°C	90.18 %	P
5	INPUT CURRENT	230V/ 1.3 A (TYP) 115V/ 2.5 A (TYP)	I/P : 230 VAC I/P : 115 VAC O/P : FULL LOAD Ta : 25°C	I = 1 A/ 230 VAC I = 1.98 A/ 115 VAC	P
6	INRUSH CURRENT	230V/ 40 A (TYP) 115V/ 20 A(TYP) COLD START	I/P : 230 VAC I/P : 115 VAC O/P : FULL LOAD Ta : 25°C	I = 28 A/ 230 VAC I = 12 A/ 115 VAC	P
7	LEAKAGE CURRENT	< 1 mA / 240 VAC	I/P : 264 VAC O/P : Min LOAD Ta : 25°C	L-FG : 0.81 mA N-FG : 0.81 mA	P

PROTECTION FUNCTION TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	OVER LOAD PROTECTION	105 % ~ 135 %	I/P : 230 VAC I/P : 115 VAC O/P : TESTING Ta : 25°C	119 %/ 230 VAC 116.6%/ 115 VAC Hiccup Mode	P
2	OVER VOLTAGE PROTECTION	CH1 : 58.4V ~ 68V	I/P : 230 VAC I/P : 115 VAC O/P : MIN LOAD Ta : 25°C	63.83V/ 230 VAC 63.76V/ 115 VAC Shut down Re- power ON	P
3	OVER TEMPERATURE PROTECTION	SPEC : TSW1 : 100±5°C O.T.P. NO DAMAGE	I/P : 230 VAC O/P : FULL LOAD	O.T.P. Active Shut down o/p voltage , recovers automatically after temperature goes down	P
4	SHORT PROTECTION	SHORT EVERY OUTPUT 1 HOUR NO DAMAGE	I/P : 264 VAC O/P : FULL LOAD Ta : 25°C	NO DAMAGE Hiccup Mode	P

COMPONENT STRESS TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	Power Transistor (D to S) or (C to E) Peak Voltage	Q3 Rated : STP14NM50N 12A/500V	I/P : High-Line +3V = 267 V O/P : (1)Full Load Turn on (2) Output Short (3)Full load continue Ta : 25°C	(1) 394 V (2) 426 V (3) 374 V	P
2	Diode Peak Voltage	Q102 Rated : FMX-12SL 10A/200V Q104 Rated : SF20LC30 20A/300V	I/P : High-Line +3V = 267 V O/P : (1)Full Load Turn on (2)Output Short (3)Full load continue (1)Full Load Turn on (2)Output Short (3)Full load continue Ta : 25°C	(1) 169 V (2) 170 V (3) 166 V (1) 253 V (2) 232 V (3) 251 V	P
4	Input Capacitor Voltage	C 5 Rated : 180u/400V 105°C 18*40 KMG (SURGE VOLTAGE 450V)	I/P : High-Line +3V = 267 V O/P : (1)Full Load Turn on /Off (2) Min load Turn on /Off (3)Full Load /Min load Change Ta : 25°C	(1) 388 V (2) 382 V (3) 420 V	P
5	Control IC Voltage Test	U 1 Rated : PWM FAN4800AUN 12V~30V	I/P : High-Line +3V = 267 V O/P : (1)Full Load Turn on /Off (2) Min load Turn on /Off (3)Full Load /Min load Change Ta : 25°C	(1) 16.2 V (2) 15.7 V (3) 16.1 V	P
6	Power Transistor (D to S) or (C to E) Peak Voltage	Q 2 Rated : STP19NM50N 13A/500V	I/P : High-Line +3V = 267 V O/P : (1)Full Load Turn on (2) Output Short (3)Full load continue Ta : 25°C	(1) 414 V (2) 406 V (3) 402 V	P

SAFETY & E.M.C. TEST

SAFETY TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	WITHSTAND VOLTAGE	I/P-O/P : 3 KVAC/min I/P-FG : 2 KVAC/min O/P-FG : 0.5 KVAC/min	I/P-O/P : 3.6 KVAC/min I/P-FG : 2.4 KVAC/min O/P-FG : 0.6 KVAC/min Ta : 25°C	I/P-O/P : 6.61 mA I/P-FG : 6 mA O/P-FG : 9.41 mA NO DAMAGE	P
2	ISOLATION RESISTANCE	I/P-O/P : 500VDC>100MΩ I/P-FG : 500VDC>100MΩ O/P-FG : 500VDC>100MΩ	I/P-O/P : 500 VDC I/P-FG : 500 VDC O/P-FG : 500 VDC Ta : 25°C / 70%RH	I/P-O/P : 30 GΩ I/P-FG : 30 GΩ O/P-FG : 30 GΩ NO DAMAGE	P
3	GROUNDING CONTINUITY	FG(PE) TO CHASSIS OR TRACE < 100 mΩ	40 A / 2min Ta : 25°C / 70%RH	9 mΩ	P

E.M.C TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT
1	HARMONIC	EN61000-3-2 CLASS A CLASS D	I/P : 230 VAC/50HZ O/P : FULL LOAD Ta : 25°C	PASS	P
2	CONDUCTION	EN55022 CLASS B	I/P : 230 VAC (50HZ) O/P : FULL/50% LOAD Ta : 25°C	PASS Test by certified Lab	P
3	RADIATION	EN55022 CLASS B	I/P : 230 VAC (50HZ) O/P : FULL LOAD Ta : 25°C	PASS Test by certified Lab	P
4	E.S.D	EN61000-4-2 LIGHT INDUSTRY AIR : 8KV / Contact : 4KV	I/P : 230 VAC/50HZ O/P : FULL LOAD Ta : 25°C	CRITERIA A	P
5	E.F.T	EN61000-4-4 LIGHT INDUSTRY INPUT : 1KV	I/P : 230 VAC/50HZ O/P : FULL LOAD Ta : 25°C	CRITERIA A	P
6	SURGE	IEC61000-4-5 LIGHT INDUSTRY L-N : 1KV L,N-PE : 2KV	I/P : 230 VAC/50HZ O/P : FULL LOAD Ta : 25°C	CRITERIA A	P
7	Test by certified Lab & Test Report Prepare				

RELIABILITY TEST

ENVIRONMENT TEST

NO	TEST ITEM	SPECIFICATION	TEST CONDITION	RESULT	VERDICT																																																																																															
1	TEMPERATURE RISE TEST	MODEL : RSP-200-24 1. ROOM AMBIENT BURN-IN : 2 HRS I/P : 230VAC O/P : FULL LOAD Ta=31.3 °C 2. HIGH AMBIENT BURN-IN : 2 HRS I/P : 230VAC O/P : FULL LOAD Ta=55.5 °C <table><tr><th>NO</th><th>Position</th><th>PART NUMBER</th><th>ROOM AMBIENT Ta= 31.3 °C</th><th>HIGH AMBIENT Ta=55.5 °C</th></tr><tr><td>1</td><td>LF1</td><td>TR1021</td><td>58.6°C</td><td>79.7°C</td></tr><tr><td>2</td><td>C10</td><td>105/450V 10% P=15 B32672P4</td><td>65.8°C</td><td>86.7°C</td></tr><tr><td>3</td><td>BD1</td><td>10A/800V GLASS KBJ1008G</td><td>62.9°C</td><td>83.4°C</td></tr><tr><td>4</td><td>D1</td><td>STTH8S06D 8A/600V</td><td>68.3°C</td><td>89.3°C</td></tr><tr><td>5</td><td>Q2</td><td>STP19NM50N 13A/500V</td><td>67.7°C</td><td>89.2°C</td></tr><tr><td>6</td><td>Q3</td><td>STP14NM50N 12A/500V</td><td>64.0°C</td><td>84.7°C</td></tr><tr><td>7</td><td>C5</td><td>180u/400V 105°C 18*40 KMG</td><td>64.0°C</td><td>81.3°C</td></tr><tr><td>8</td><td>L1</td><td>TR1022</td><td>85.5°C</td><td>106.3°C</td></tr><tr><td>9</td><td>U1</td><td>FAN4800AUN</td><td>63.1°C</td><td>84.0°C</td></tr><tr><td>10</td><td>T2</td><td>TR1048</td><td>60.9°C</td><td>78.0°C</td></tr><tr><td>11</td><td>C18</td><td>47u/50V L5Kh 6.3*11 YXF</td><td>79.5°C</td><td>101.2°C</td></tr><tr><td>12</td><td>T1 COIL</td><td>TF2438</td><td>93.8°C</td><td>113.9°C</td></tr><tr><td>13</td><td>TSW1</td><td>100°C</td><td>66.6°C</td><td>88.1°C</td></tr><tr><td>14</td><td>RTH2</td><td>5KΩ 5Φ TDC05C20J 5%</td><td>74.8°C</td><td>95.7°C</td></tr><tr><td>15</td><td>Q101</td><td>STPS20120CT 20A/120V</td><td>79.0°C</td><td>99.3°C</td></tr><tr><td>16</td><td>Q104</td><td>STPS20120CT 20A/120V</td><td>69.2°C</td><td>91.3°C</td></tr><tr><td>17</td><td>L100</td><td>TR1064</td><td>80.8°C</td><td>102.5°C</td></tr><tr><td>18</td><td>C105</td><td>1000u/35V UL10Kh 12.5*20 ZLH</td><td>60.9°C</td><td>81.9°C</td></tr></table>			NO	Position	PART NUMBER	ROOM AMBIENT Ta= 31.3 °C	HIGH AMBIENT Ta=55.5 °C	1	LF1	TR1021	58.6°C	79.7°C	2	C10	105/450V 10% P=15 B32672P4	65.8°C	86.7°C	3	BD1	10A/800V GLASS KBJ1008G	62.9°C	83.4°C	4	D1	STTH8S06D 8A/600V	68.3°C	89.3°C	5	Q2	STP19NM50N 13A/500V	67.7°C	89.2°C	6	Q3	STP14NM50N 12A/500V	64.0°C	84.7°C	7	C5	180u/400V 105°C 18*40 KMG	64.0°C	81.3°C	8	L1	TR1022	85.5°C	106.3°C	9	U1	FAN4800AUN	63.1°C	84.0°C	10	T2	TR1048	60.9°C	78.0°C	11	C18	47u/50V L5Kh 6.3*11 YXF	79.5°C	101.2°C	12	T1 COIL	TF2438	93.8°C	113.9°C	13	TSW1	100°C	66.6°C	88.1°C	14	RTH2	5KΩ 5Φ TDC05C20J 5%	74.8°C	95.7°C	15	Q101	STPS20120CT 20A/120V	79.0°C	99.3°C	16	Q104	STPS20120CT 20A/120V	69.2°C	91.3°C	17	L100	TR1064	80.8°C	102.5°C	18	C105	1000u/35V UL10Kh 12.5*20 ZLH	60.9°C	81.9°C	P
NO	Position	PART NUMBER	ROOM AMBIENT Ta= 31.3 °C	HIGH AMBIENT Ta=55.5 °C																																																																																																
1	LF1	TR1021	58.6°C	79.7°C																																																																																																
2	C10	105/450V 10% P=15 B32672P4	65.8°C	86.7°C																																																																																																
3	BD1	10A/800V GLASS KBJ1008G	62.9°C	83.4°C																																																																																																
4	D1	STTH8S06D 8A/600V	68.3°C	89.3°C																																																																																																
5	Q2	STP19NM50N 13A/500V	67.7°C	89.2°C																																																																																																
6	Q3	STP14NM50N 12A/500V	64.0°C	84.7°C																																																																																																
7	C5	180u/400V 105°C 18*40 KMG	64.0°C	81.3°C																																																																																																
8	L1	TR1022	85.5°C	106.3°C																																																																																																
9	U1	FAN4800AUN	63.1°C	84.0°C																																																																																																
10	T2	TR1048	60.9°C	78.0°C																																																																																																
11	C18	47u/50V L5Kh 6.3*11 YXF	79.5°C	101.2°C																																																																																																
12	T1 COIL	TF2438	93.8°C	113.9°C																																																																																																
13	TSW1	100°C	66.6°C	88.1°C																																																																																																
14	RTH2	5KΩ 5Φ TDC05C20J 5%	74.8°C	95.7°C																																																																																																
15	Q101	STPS20120CT 20A/120V	79.0°C	99.3°C																																																																																																
16	Q104	STPS20120CT 20A/120V	69.2°C	91.3°C																																																																																																
17	L100	TR1064	80.8°C	102.5°C																																																																																																
18	C105	1000u/35V UL10Kh 12.5*20 ZLH	60.9°C	81.9°C																																																																																																
2	OVER LOAD BURN-IN TEST	NO DAMAGE 1 HOUR (MIN)	I/P : 230 VAC O/P : 119 % LOAD Ta : 25°C	TEST : OK	P																																																																																															
3	LOW TEMPERATURE TURN ON TEST	TURN ON AFTER 2 HOUR	I/P : 264VAC/100VAC O/P : 100 % LOAD Ta= -35 °C	TEST : OK	P																																																																																															
4	HIGH HUMIDITY HIGH TEMPERATURE HIGH VOLTAGE TURN ON TEST	AFTER 12 HOURS IN CHAMBER ON CONTROL 45 °C NO DAMAGE	I/P : 272 VAC O/P : FULL LOAD Ta= 45 °C HUMIDITY= 95 %R.H	TEST : OK	P																																																																																															
5	TEMPERATURE COEFFICIENT	±0.03 %/°C (0~50°C)	I/P : 230 VAC O/P : FULL LOAD	±0 %/°C (0~50°C)	P																																																																																															
6	STORAGE TEMPERATURE TEST	1. Thermal shock Temperature : -45°C~ +90°C 2. Temperature change rate : 25°C / MIN 3. Dwell time low and high temperature : 30 MIN/EACH 4. Total test cycle : 5 CYCLE 5. Input/Output condition : STATIC		OK	P																																																																																															

7	THERMAL SHOCK TEST	1. Thermal shock Temperature : -35℃~ +50℃ 2. Temperature change rate : 25℃ / MIN 3. Dwell time low and high temperature : 30 MIN/EACH 4. Total test cycle : 10 CYCLE 5. Input/Output condition : 230VAC/Full Load AC ON/OFF TEST turn on 58sec ; turn off 2sec	OK	P
8	VIBRATION TEST	1 Carton & 1 Set (1) Waveform : Sine Wave (2) Frequency : 10~500Hz (3) Sweep Time : 12min/sweep cycle (4) Acceleration : 2G (5) Test Time : 60min in each axis (X.Y.Z) (6) Ta : 25℃	TEST : OK	P
9	CAPACITOR LIFE CYCLE	RSP-200-24:SUPPOSE C105 IS THE MOST CRITICAL COMPONENT (1) I/P : 230VAC O/P : FULL LOAD Ta= 25 °C LIFE TIME (2) I/P : 230VAC O/P : FULL LOAD Ta=45 °C LIFE TIME (3) I/P : 230VAC O/P : 75% LOAD Ta= 45 °C LIFE TIME (4) I/P : 230VAC O/P : 50% LOAD Ta= 45 °C LIFE TIME	(1) 405511HRS (2) 122277HRS (3) 165852HRS (4) 217260HRS	P
10	MTBF	MIL-HDBK-217F NOTICE S2 PARTS COUNT TOTAL FAILURE RATE : 224.5 KHRS		P
11	DMTBF/Accelerated Life Test	Demonstration Mean Time Between Failure (Expected Life): Above 30,000 hours @ TA 45℃		P

DATE	SAMPLE	TEST RESULT	TESTER	APPROVAL
2012/8/30	RD SAMPLE	PASS	SANFORD SU	VINCENT TSENG
2012/10/17	PRODUCT SAMPLE	PASS	SANFORD SU	VINCENT TSENG

2009/08/04 A50-F023