



Test Report : DDRH-30-12

30W High Reliable 150~1500Vdc Ultra Wide Input DC-DC Converter

■ DESIGN VERIFY TEST

Output Function Test

Input Function Test

Protection Function Test

■ SAFETY TEST

Safety Test

■ RELIABILITY TEST

Environment Test

DESIGN VERIFY TEST

OUTPUT FUNCTION TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDITC
1	VOLTAGE ACCURACY	-2.0% ~ +2.0 %	I/P:800VDC O/P:FULL LOAD Ta:25°C	-0.02%	P
2	RIPPLE & NOISE	100 mVp-p	I/P:800VDC O/P:FULL LOAD Ta:25°C	60mV	P
3	LINE REGULATION	-1.0% ~ +1.0%	I/P:150VDC~1500VDC O/P: FULL LOAD Ta:25°C	-0.03% ~ -0.13%	P
4	LOAD REGULATION	-1.0% ~ +1.0%	I/P:800VDC O/P:10% LOAD~FULL LOAD Ta:25°C	-0.09% ~ +0.08%	P
5	HOLD UP TIME	16ms min.	I/P:800VDC O/P:FULL LOAD Ta:25°C	50.4ms	P
6	SETUP TIME	2s max.	I/P:800VDC O/P: FULL LOAD Ta:25°C	84.8ms	P

INPUT FUNCTION TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDITC
1	INPUT VOLTAGE RANGE	150 VDC ~1500 VDC	I/P:TESTING O/P:FULL LOAD Ta:25°C	127.3VDC ~1500 VDC	P
2	EFFICIENCY	85%	I/P:800VDC O/P:FULL LOAD Ta:25°C	91.92%	P
3	DC CURRENT	50mA / FULL LOAD 0.2mA / NO LOAD	I/P:800VDC O/P:NO / FULL LOAD Ta:25°C	40.5mA / FULL LOAD 0.159 mA / NO LOAD	P

PROTECTION FUNCTION TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDITC
1	SHORT PROTECTION	CONTINUOUS	I/P:1500VDC O/P:FULL LOAD Ta:25°C	HICCUP MODE AUTO-RECOVER	P
2	OVER LOAD PROTECTION	110% ~ 300%	I/P:800VDC O/P:TESTING Ta:25°C	170.0% HICCUP MODE AUTO-RECOVER	P
3	OVER VOLTAGE PROTECTION	YES	I/P:800VDC O/P: MIN LOAD Ta:25°C	HICCUP MODE AUTO-RECOVER	P

4	DC INPUT REVERSE POLARITY	NO DAMAGE	I/P:800VDC O/P: FULL LOAD Ta:25°C	NO DAMAGE	P
5	UNDER VOLTAGE LOCKOUT	START-UP VOLTAGE 144Vdc(max) SHUTDOWN VOLTAGE 132Vdc(min)	I/P: TESTING O/P: FULL LOAD Ta:25°C	136.9VDC 127.3VDC	P

SAFETY TEST

SAFETY TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDITC
1	WITHSTAND VOLTAGE	I/P-O/P:4.0KVAC/min	I/P-O/P:4.0KVAC/min Ta:25°C	I/P-O/P: 0.002mA NO DAMAGE	P
2	ISOLATION RESISTANCE	I/P-O/P:500VDC>1000MΩ	I/P-O/P:500 VDC Ta:25°C	I/P-O/P>1000MΩ NO DAMAGE	P

RELIABILITY TEST

ENVIRONMENT TEST

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDITC
1	TEMPERATURE RISE TEST	1. ROOM AMBIENT BURN-IN : 4HRS I/P:800VDC O/P:FULL LOAD Ta=25°C 2. HIGH AMBIENT BURN-IN : 4HRS I/P:800VDC O/P:FULL LOAD Ta=50°C 3. HIGH AMBIENT BURN-IN : 4HRS I/P:800VDC O/P:50% LOAD Ta=70°C			P

2	LOW TEMPERATURE TURN ON TEST	TURN ON AFTER 4 HOURS	I/P:800VDC O/P: FULL LOAD Ta= -40℃	TEST : OK	P
---	------------------------------	-----------------------	--	-----------	---

OTHER

NO	TEST ITEM	SPECICATION	TEST CONDITION	RESULT	VERDITC
1	MTBF	MIL-HDBK-217F,GB,25℃ TOTAL FAILURE RATE : M.T.B.F : 318K HRS			P

TEST RESULT	TESTER	APPROVAL
PASS	ARCHEN HSIAO	PETER CHENG