



|                   |                                                 |
|-------------------|-------------------------------------------------|
| Material          | Polyamide V0 according to UL94                  |
| Seal              | NBR                                             |
| Protection class  | IP 68 – 10 bar / IP 69 K with additional O-ring |
| NEMA type rating  | 4 / 4X / 6                                      |
| Temperature range | -40°C to +100°C                                 |
| Colour            | grey / black / blue                             |
| RAL               | 7035 / 9005 / 5012                              |

RoHS

// With additional premounted O-ring on request

// Other sealing material e.g. Silicone on request

| AG      | Øk<br>mm | GL<br>mm | H<br>mm | SW1/SW2<br>mm | ⌀<br>Nm | Item-No<br>grey | Item-No<br>black | Item-No<br>blue |
|---------|----------|----------|---------|---------------|---------|-----------------|------------------|-----------------|
| PG 7    | 2 – 5    | 8        | 21      | 15/15         | 1.5     | 1.209.0700.15   | 1.209.0701.15    | 1.209.0702.15   |
| PG 7    | 3 – 6.5  | 8        | 21      | 15/15         | 1.5     | 1.209.0700.14   | 1.209.0701.14    | 1.209.0702.14   |
| PG 9    | 2 – 6    | 8        | 22      | 19/19         | 2       | 1.209.0900.15   | 1.209.0901.15    | 1.209.0902.15   |
| PG 9    | 4 – 8    | 8        | 22      | 19/19         | 2       | 1.209.0900.14   | 1.209.0901.14    | 1.209.0902.14   |
| PG 11   | 3 – 7    | 8        | 25      | 22/22         | 2.5     | 1.209.1100.15   | 1.209.1101.15    | 1.209.1102.15   |
| PG 11   | 5 – 10   | 8        | 25      | 22/22         | 3       | 1.209.1100.14   | 1.209.1101.14    | 1.209.1102.14   |
| PG 13.5 | 5 – 9    | 9        | 27      | 24/24         | 3       | 1.209.1300.15   | 1.209.1301.15    | 1.209.1302.15   |
| PG 13.5 | 6 – 12   | 9        | 27      | 24/24         | 4.5     | 1.209.1300.14   | 1.209.1301.14    | 1.209.1302.14   |
| PG 16   | 7 – 12   | 10       | 28      | 27/27         | 3.5     | 1.209.1600.15   | 1.209.1601.15    | 1.209.1602.15   |
| PG 16   | 10 – 14  | 10       | 28      | 27/27         | 4.5     | 1.209.1600.14   | 1.209.1601.14    | 1.209.1602.14   |
| PG 21   | 9 – 16   | 11       | 31      | 33/33         | 4       | 1.209.2100.15   | 1.209.2101.15    | 1.209.2102.15   |
| PG 21   | 13 – 18  | 11       | 31      | 33/33         | 5       | 1.209.2100.14   | 1.209.2101.14    | 1.209.2102.14   |
| PG 29   | 13 – 20  | 11       | 39      | 42/42         | 6       | 1.209.2900.15   | 1.209.2901.15    | 1.209.2902.15   |
| PG 29   | 18 – 25  | 11       | 39      | 42/42         | 6.5     | 1.209.2900.14   | 1.209.2901.14    | 1.209.2902.14   |
| PG 36   | 20 – 26  | 13       | 48      | 53/53         | 9       | 1.209.3600.15   | 1.209.3601.15    | 1.209.3602.15   |
| PG 36   | 22 – 32  | 13       | 48      | 53/53         | 10      | 1.209.3600.14   | 1.209.3601.14    | 1.209.3602.14   |
| PG 42   | 25 – 31  | 13       | 49      | 60/60         | 11      | 1.209.4200.15   | 1.209.4201.15    | 1.209.4202.15   |
| PG 42   | 32 – 38  | 13       | 49      | 60/60         | 15      | 1.209.4200.14   | 1.209.4201.14    | 1.209.4202.14   |
| PG 48   | 29 – 35  | 14       | 49      | 65/65         | 12      | 1.209.4800.15   | 1.209.4801.15    | 1.209.4802.15   |
| PG 48   | 37 – 44  | 14       | 49      | 65/65         | 18      | 1.209.4800.14   | 1.209.4801.14    | 1.209.4802.14   |

