



Material	Polyamide V0 according to UL94
Seal	NBR
Protection class	IP 68 – 10 bar / IP 69 K with additional O-ring
NEMA type rating	4 / 4X / 6
Temperature range	-40°C to +100°C
Colour	grey / black / blue
RAL	7035 / 9005 / 5012

RoHS

// With additional premounted O-ring on request

// Other sealing material e.g. Silicone on request

AG	Øk mm	GL mm	H mm	SW1/SW2 mm	⌀ Nm	Item-No grey	Item-No black	Item-No blue
M12 x 1.5	2 – 5	8	21	15/15	1.5	1.209.1200.51	1.209.1201.51	1.209.1202.51
M12 x 1.5	3 – 6.5	8	21	15/15	1.5	1.209.1200.50	1.209.1201.50	1.209.1202.50
M16 x 1.5	2 – 6	8	22	19/19	2	1.209.1600.51	1.209.1601.51	1.209.1602.51
M16 x 1.5	4 – 8	8	22	19/19	2	1.209.1600.50	1.209.1601.50	1.209.1602.50
M16 x 1.5	5 – 10	8	25	22/22	3	1.219.1600.50	1.219.1601.50	1.219.1602.50
M20 x 1.5	5 – 9	9	27	24/24	3	1.209.2000.51	1.209.2001.51	1.209.2002.51
M20 x 1.5	6 – 12	9	27	24/24	4.5	1.209.2000.50	1.209.2001.50	1.209.2002.50
M20 x 1.5	10 – 14	9	28	27/27	4.5	1.219.2000.50	1.219.2001.50	1.219.2002.50
M25 x 1.5	9 – 16	11	31	33/33	4	1.209.2500.51	1.209.2501.51	1.209.2502.51
M25 x 1.5	13 – 18	11	31	30/30	5	1.219.2500.50	1.219.2501.50	1.219.2502.50
M25 x 1.5	13 – 18	11	31	33/33	5	1.209.2500.50	1.209.2501.50	1.209.2502.50
M32 x 1.5	13 – 20	11	39	42/42	6	1.209.3200.51	1.209.3201.51	1.209.3202.51
M32 x 1.5	14 – 21	11	39	36/36	6	1.219.3200.50	1.219.3201.50	1.219.3202.50
M32 x 1.5	18 – 25	11	39	42/42	6.5	1.209.3200.50	1.209.3201.50	1.209.3202.50
M40 x 1.5	19 – 27	13	47	46/46	9	1.219.4000.50	1.219.4001.50	1.219.4002.50
M40 x 1.5	20 – 26	13	48	53/53	9	1.209.4000.51	1.209.4001.51	1.209.4002.51
M40 x 1.5	22 – 32	13	48	53/53	10	1.209.4000.50	1.209.4001.50	1.209.4002.50
M50 x 1.5	25 – 31	13	49	60/60	11	1.209.5000.51	1.209.5001.51	1.209.5002.51
M50 x 1.5	32 – 38	13	49	60/60	15	1.209.5000.50	1.209.5001.50	1.209.5002.50
M63 x 1.5	29 – 35	14	49	65/68	12	1.209.6300.51	1.209.6301.51	1.209.6302.51
M63 x 1.5	37 – 44	14	49	65/68	18	1.209.6300.50	1.209.6301.50	1.209.6302.50

