


Plastic cable glands

HSK-K (metric-long)



Material	Polyamide V0 according to UL94
Seal	NBR
Protection class	IP 68 – 10 bar / IP 69 K with additional o-ring
NEMA type rating	4 / 4X / 6
Temperature range	-40°C to +100°C
Colour	black / blue / grey
RAL	9005 / 5012 / 7035

RoHS

// With additional premounted O-ring on request

// Other sealing material e.g. Silicone on request

AG	∅k mm	GL mm	H mm	SW1/SW2 mm	⌀ Nm	Item-No grey	Item-No black	Item-No blue
M12 x 1.5	2 – 5	15	21	15/15	1.5	1.209.1200.31	1.209.1201.31	1.209.1202.31
M12 x 1.5	3 – 6.5	15	21	15/15	1.5	1.209.1200.30	1.209.1201.30	1.209.1202.30
M16 x 1.5	2 – 6	15	22	19/19	2	1.209.1600.31	1.209.1601.31	1.209.1602.31
M16 x 1.5	4 – 8	15	22	19/19	2	1.209.1600.30	1.209.1601.30	1.209.1602.30
M16 x 1.5	5 – 10	15	25	22/22	3	1.219.1600.30	1.219.1601.30	1.219.1602.30
M20 x 1.5	5 – 9	15	27	24/24	3	1.209.2000.31	1.209.2001.31	1.209.2002.31
M20 x 1.5	6 – 12	15	27	24/24	4.5	1.209.2000.30	1.209.2001.30	1.209.2002.30
M20 x 1.5	10 – 14	15	28	27/27	4.5	1.219.2000.30	1.219.2001.30	1.219.2002.30
M25 x 1.5	9 – 16	15	31	33/33	4	1.209.2500.31	1.209.2501.31	1.209.2502.31
M25 x 1.5	13 – 18	15	31	33/33	5	1.209.2500.30	1.209.2501.30	1.209.2502.30
M32 x 1.5	13 – 20	15	39	42/42	6	1.209.3200.31	1.209.3201.31	1.209.3202.31
M32 x 1.5	18 – 25	15	39	42/42	6.5	1.209.3200.30	1.209.3201.30	1.209.3202.30
M40 x 1.5	20 – 26	18	48	53/53	9	1.209.4000.31	1.209.4001.31	1.209.4002.31
M40 x 1.5	22 – 32	18	48	53/53	10	1.209.4000.30	1.209.4001.30	1.209.4002.30
M50 x 1.5	25 – 31	18	49	60/60	11	1.209.5000.31	1.209.5001.31	1.209.5002.31
M50 x 1.5	32 – 38	18	49	60/60	15	1.209.5000.30	1.209.5001.30	1.209.5002.30
M63 x 1.5	29 – 35	18	49	65/68	12	1.209.6300.31	1.209.6301.31	1.209.6302.31
M63 x 1.5	37 – 44	18	49	65/68	18	1.209.6300.30	1.209.6301.30	1.209.6302.30

