


Ex-Kabelverschraubungen

HSK-INOX-PVDF-Ex (metrisch, PG)



Material	INOX 1.4305
Klemmeinsatz	PVDF
Formdichtung	FKM
Material O-Ring	FKM
Schutzart	IP 68 – 10 bar / IP 69 K
Ex-Schutzstufe	II 2G Ex eb IIC Gb / II 1D Ex ta IIIC Da
NEMA Type Rating	4 / 4X / 6
Temperaturbereich	-20°C bis +130°C

RoHS

AG	∅k mm	GL mm	H mm	SW1/SW2 mm	Nm	Art.-Nr.
M12 x 1,5	2 – 5	6,5	19	14/14	4	1.662.1200.51
M12 x 1,5	3 – 6,5	6,5	19	14/14	4	1.662.1200.50
M16 x 1,5	3 – 7	6	22	22/22	5	1.662.1600.51
M16 x 1,5	5 – 10	6	22	22/22	5	1.662.1600.50
M20 x 1,5	7 – 12	6	23	24/24	10	1.662.2000.51
M20 x 1,5	10 – 14	6	23	24/24	10	1.662.2000.50
M25 x 1,5	9 – 16	7	24	30/30	12	1.662.2500.51
M25 x 1,5	13 – 18	7	24	30/30	12	1.662.2500.50
M32 x 1,5	13 – 20	8	29	41/41	15	1.662.3200.51
M32 x 1,5	20 – 25	8	29	41/41	15	1.662.3200.50
M40 x 1,5	20 – 26	8	35	50/50	15	1.662.4000.51
M40 x 1,5	22 – 32	8	35	50/50	15	1.662.4000.50
PG 7	2 – 5	5	19	14/14	4	1.662.0700.15
PG 7	3 – 6,5	5	19	14/14	4	1.662.0700.01
PG 9	2 – 6	6	21	17/17	6	1.662.0900.15
PG 9	4 – 8	6	21	17/17	6	1.662.0900.01
PG 11	3 – 7	6	22	22/22	5	1.662.1100.15
PG 11	5 – 10	6	22	22/22	5	1.662.1100.01
PG 13,5	5 – 9	6	24	22/22	8	1.662.1300.15
PG 13,5	7 – 12	6	24	22/22	8	1.662.1300.01
PG 16	7 – 12	6	23	24/24	10	1.662.1600.15
PG 16	10 – 14	6	23	24/24	10	1.662.1600.01
PG 21	9 – 16	7	24	30/30	12	1.662.2100.15
PG 21	13 – 18	7	24	30/30	12	1.662.2100.01
PG 29	13 – 20	8	29	41/41	15	1.662.2900.15
PG 29	20 – 25	8	29	41/41	15	1.662.2900.01
PG 36	20 – 26	8	35	50/50	15	1.662.3600.15
PG 36	22 – 32	8	35	50/50	15	1.662.3600.01



zur Montageanleitung

