


Ex-Kabelverschraubungen

HSK-K-Ex-Active (metrisch/-lang)



Material	Polyamid, glasfaserverstärkt
Formdichtung	NBR
Material O-Ring	NBR
Schutzart	IP 68 – 10 bar
Ex-Schutzstufe	II 2G Ex eb IIC Gb / II 1D Ex ta IIIC Da / Class I Div 2 Groups A,B,C,D / Class II Div 1 Groups E,F,G
Temperaturbereich	-20°C bis +85°C
Farbe	schwarz / blau-schwarz
RAL	9005 / 5012

RoHS

AG	Øk mm	H mm	SW1/SW2 mm	⌀ Nm	GL mm	Art.-Nr. schwarz kurz	Art.-Nr. blau-schwarz kurz	GL mm	Art.-Nr. schwarz lang	Art.-Nr. blau-schwarz lang
M12 x 1,5	2 – 5	21	15/15	2	8	1.292.1201.51	1.292.1202.51	15	1.292.1201.31	1.292.1202.31
M12 x 1,5	3 – 6,5	21	15/15	1,5	8	1.292.1201.50	1.292.1202.50	15	1.292.1201.30	1.292.1202.30
M16 x 1,5	3 – 6	22	19/19	2	8	1.292.1601.51	1.292.1602.51	15	1.292.1601.31	1.292.1602.31
M16 x 1,5	3 – 7	25	22/22	3	8	1.292.1611.51	1.292.1612.51	15	1.292.1611.31	1.292.1612.31
M16 x 1,5	4 – 8	22	19/19	2	8	1.292.1601.50	1.292.1602.50	15	1.292.1601.30	1.292.1602.30
M16 x 1,5	5 – 10	25	22/22	3	8	1.292.1611.50	1.292.1612.50	15	1.292.1611.30	1.292.1612.30
M20 x 1,5	5 – 9	27	24/24	4,5	9	1.292.2001.51	1.292.2002.51	15	1.292.2001.31	1.292.2002.31
M20 x 1,5	6 – 12	27	24/24	4,5	9	1.292.2001.50	1.292.2002.50	15	1.292.2001.30	1.292.2002.30
M20 x 1,5	7 – 12	28	27/27	4,5	9	1.292.2016.51	1.292.2017.51	15	1.292.2016.31	1.292.2017.31
M20 x 1,5	10 – 14	28	27/27	4,5	9	1.292.2016.50	1.292.2017.50	15	1.292.2016.30	1.292.2017.30
M25 x 1,5	9 – 16	31	33/33	5	11	1.292.2501.51	1.292.2502.51	15	1.292.2501.31	1.292.2502.31
M25 x 1,5	13 – 18	31	33/33	5	11	1.292.2501.50	1.292.2502.50	15	1.292.2501.30	1.292.2502.30
M32 x 1,5	13 – 20	39	42/42	6,5	11	1.292.3201.51	1.292.3202.51	15	1.292.3201.31	1.292.3202.31
M32 x 1,5	18 – 25	39	42/42	6,5	11	1.292.3201.50	1.292.3202.50	15	1.292.3201.30	1.292.3202.30
M40 x 1,5	20 – 26	48	53/53	10	13	1.292.4001.51	1.292.4002.51	18	1.292.4001.31	1.292.4002.31
M40 x 1,5	22 – 32	48	53/53	10	13	1.292.4001.50	1.292.4002.50	18	1.292.4001.30	1.292.4002.30
M50 x 1,5	25 – 31	49	60/60	15	13	1.292.5001.51	1.292.5002.51	18	1.292.5001.31	1.292.5002.31
M50 x 1,5	32 – 38	49	60/60	15	13	1.292.5001.50	1.292.5002.50	18	1.292.5001.30	1.292.5002.30
M63 x 1,5	29 – 35	49	65/68	22	14	1.292.6301.51	1.292.6302.51	18	1.292.6301.31	1.292.6302.31
M63 x 1,5	37 – 44	49	65/68	22	14	1.292.6301.50	1.292.6302.50	18	1.292.6301.30	1.292.6302.30



zur Montageanleitung

