



Material	Polyamid, glasfaserverstärkt
Material O-Ring	NBR
Schutzart	IP 68 – 10 bar / IP 69 K
Ex-Schutzstufe	II 1D Ex ta IIIC Da / II 2G Ex e IIC Gb
Temperaturbereich	-20°C bis +90°C
Farbe	schwarz
RAL	9005

RoHS

AG	D mm	GL mm	H mm	SW mm	⊙	Art.-Nr.
M12 x 1,5	16,5	8,5	13	15	6	1.297.1201.50
M16 x 1,5	20,5	8,5	13	19	8	1.297.1601.50
M20 x 1,5	25,5	9	14,5	24	8	1.297.2001.50
M25 x 1,5	30,5	10,5	16	28	8	1.297.2501.50
M32 x 1,5	38	11,5	17,5	36	8	1.297.3201.50
M40 x 1,5	48	11,5	18	46	8	1.297.4001.50
M50 x 1,5	60	13,5	20	55	8	1.297.5001.50
M63 x 1,5	75	14,5	21	70	8	1.297.6301.50
PG 7	16,5	8,5	13	15	6	1.297.0701.11
PG 9	20,5	8,5	13	19	8	1.297.0901.11
PG 11	25,5	9	14,5	24	8	1.297.1101.11
PG 13,5	25,5	9	14,5	24	8	1.297.1301.11
PG 16	30,5	10,5	16	28	8	1.297.1601.11
PG 21	38	11,5	17,5	36	8	1.297.2101.11
PG 29	48	11,5	18	46	8	1.297.2901.11
PG 36	60	13,5	20	55	8	1.297.3601.11
PG 42	65	13,5	20	60	8	1.297.4201.11
PG 48	75	14,5	21	70	8	1.297.4801.11



zur Montageanleitung

