


Material	NBR / FKM / VMQ (Silikon)
Temperaturbereich	-30°C bis +100°C / -20°C bis +200°C / -60°C bis +200°C

RoHS



passend zu AG	d mm	s mm	Art.-Nr. NBR	Art.-Nr. FKM	Art.-Nr. VMQ (Silikon)
M12 x 1,5	10	1,5	1.321.1200.57	1.321.1200.58	1.321.1200.59
M16 x 1,5	12	1,5	1.321.1600.57	1.321.1600.58	1.321.1600.59
M20 x 1,5	17	1,8	1.321.2000.57	1.321.2000.58	1.321.2000.59
M25 x 1,5	22	2	1.321.2500.57	1.321.2500.58	1.321.2500.59
M32 x 1,5	29	2	1.321.3200.57	1.321.3200.58	1.321.3200.59
M40 x 1,5	35	2	1.321.4000.57	1.321.4000.58	1.321.4000.59
M50 x 1,5	43	2	1.321.5000.57	1.321.5000.58	1.321.5000.59
M63 x 1,5	55	2	1.321.6300.57	1.321.6300.58	1.321.6300.59
PG 7	10	1,5	1.321.0700.17	1.321.0700.21	1.321.0700.22
PG 9	12	1,5	1.321.0900.17	1.321.0900.21	1.321.0900.22
PG 11	16	1,5	1.321.1100.17	1.321.1100.21	1.321.1100.22
PG 13,5	17	1,8	1.321.1300.17	1.321.1300.21	1.321.1300.22
PG 16	18	1,5	1.321.1600.17	1.321.1600.21	1.321.1600.22
PG 21	26	2	1.321.2100.17	1.321.2100.21	1.321.2100.22
PG 29	33	2	1.321.2900.17	1.321.2900.21	1.321.2900.22
PG 36	43	2	1.321.3600.17	1.321.3600.21	1.321.3600.22
PG 42	50	2	1.321.4200.17	1.321.4200.21	1.321.4200.22
PG 48	55	2	1.321.4800.17	1.321.4800.21	1.321.4800.22
NPT 3/8"	13	2	1.321.3800.77	1.321.3800.78	1.321.3800.79
NPT 1/2"	19	1,8	1.321.1200.77	1.321.1200.78	1.321.1200.79
NPT 3/4"	25	2			1.321.3400.79
NPT 3/4"	25	2,5	1.321.3400.77	1.321.3400.78	
NPT 1"	29	2			1.321.1000.79
NPT 1"	30	2,5	1.321.1000.77	1.321.1000.78	
NPT 1 1/4"	38	2,5	1.321.5400.77	1.321.5400.78	1.321.5400.79
NPT 1 1/2"	45	2,5	1.321.6400.77	1.321.6400.78	1.321.6400.79