



Material	INOX 1.4404 / INOX 1.4305
Klemmeinsatz	Polyamid VO nach UL94
Formdichtung	NBR
Material O-Ring	NBR
Schutzart	IP 68 – 10 bar / IP 69 K
NEMA Type Rating	4 / 4X / 6
Temperaturbereich	-40°C bis +100°C

AG	∅k mm	GL mm	H mm	SW1/SW2 mm	⌀ Nm	Art.-Nr. INOX 1.4404	Art.-Nr. INOX 1.4305
M12 x 1,5	2 – 5	6,5	19	14/14	4	1.675.1200.51	1.695.1200.51
M12 x 1,5	3 – 6,5	6,5	19	14/14	4	1.675.1200.50	1.695.1200.50
M16 x 1,5	3 – 7	6	22	22/22	5	1.675.1600.51	1.695.1600.51
M16 x 1,5	5 – 10	6	22	22/22	5	1.675.1600.50	1.695.1600.50
M20 x 1,5	7 – 12	6	23	24/24	10	1.675.2000.51	1.695.2000.51
M20 x 1,5	10 – 14	6	23	24/24	10	1.675.2000.50	1.695.2000.50
M25 x 1,5	9 – 16	7	24	30/30	12	1.675.2500.51	1.695.2500.51
M25 x 1,5	13 – 18	7	24	30/30	12	1.675.2500.50	1.695.2500.50
M32 x 1,5	13 – 20	8	31	41/41	15	1.675.3200.51	1.695.3200.51
M32 x 1,5	18 – 25	8	31	41/41	15	1.675.3200.50	1.695.3200.50
M40 x 1,5	20 – 26	8	37	50/50	15	1.675.4000.51	1.695.4000.51
M40 x 1,5	22 – 32	8	37	50/50	15	1.675.4000.50	1.695.4000.50
M50 x 1,5	25 – 31	9	37	60/60	24	1.675.5000.51	1.695.5000.51
M50 x 1,5	32 – 38	9	37	60/60	24	1.675.5000.50	1.695.5000.50
M63 x 1,5	29 – 35	10	38	64/68	30	1.675.6300.51	1.695.6300.51
M63 x 1,5	37 – 44	10	38	64/68	30	1.675.6300.50	1.695.6300.50