


Ex-Kabelverschraubungen

HSK-K-MZ-Ex (metrisch, PG)



Material	Polyamid
Formdichtung	NBR
Material O-Ring	NBR
Schutzart	IP 68 – 10 bar / IP 69 K
Ex-Schutzstufe	II 2G Ex eb IIC Gb / II 1D Ex ta IIIC Da
Temperaturbereich	-20°C bis +70°C
Farbe	schwarz
RAL	9005

RoHS

AG	Øk mm	GL mm	H mm	SW1/SW2 mm	 Nm	Art.-Nr.
M16 x 1,5	4 – 8	15	29	19/19	3	1.215.1601.50
M20 x 1,5	7 – 12	15	35,5	24/24	3,5	1.215.2001.50
M25 x 1,5	13 – 18	11	41	33/33	5	1.215.2501.50
M32 x 1,5	18 – 25	11	49	42/42	6,5	1.215.3201.50
M40 x 1,5	22 – 32	13	58	53/53	10	1.215.4001.50
M50 x 1,5	32 – 38	13	61,5	60/60	15	1.215.5001.50
M63 x 1,5	37 – 44	14	62	65/68	18	1.215.6301.50
PG 9	4 – 8	15	29	19/19	3	1.215.0901.14
PG 11	5 – 10	15	32,5	22/22	3,5	1.215.1101.14
PG 13,5	7 – 12	15	35,5	24/24	3,5	1.215.1301.14
PG 16	10 – 14	10	37,5	27/27	5	1.215.1601.14
PG 21	13 – 18	11	41	33/33	5	1.215.2101.14
PG 29	18 – 25	11	49	42/42	6,5	1.215.2901.14
PG 36	22 – 32	13	58	53/53	10	1.215.3601.14
PG 42	32 – 38	13	61,5	60/60	15	1.215.4201.14
PG 48	37 – 44	14	62	65/65	18	1.215.4801.14



zur Montageanleitung

