


Ex-Kabelverschraubungen

HSK-M-Ex (metrisch-lang)



Material	Messing vernickelt
Klemmeinsatz	Polyamid VO nach UL94
Formdichtung	NBR
Material O-Ring	NBR
Schutzart	IP 68 – 10 bar / IP 69 K
Ex-Schutzstufe	II 2G Ex eb IIC Gb / II 1D Ex ta IIIC Da
NEMA Type Rating	4 / 4X / 6
Temperaturbereich	-20°C bis +95°C / -60°C bis +95°C

RoHS

AG	Øk mm	GL mm	H mm	SW1/SW2 mm	⌚ Nm	Art.-Nr. -20°C bis +95°C	Art.-Nr. -60°C bis +95°C
M12 x 1,5	2 – 5	10	19	14/14	4	1.610.1200.31	1.640.1200.31
M12 x 1,5	3 – 6,5	10	19	14/14	4	1.610.1200.30	1.640.1200.30
M16 x 1,5	2 – 6	10	21	17/19	6	1.610.1600.31	1.640.1600.31
M16 x 1,5	3 – 7	10	22	20/20	5	1.610.1611.31	1.640.1611.31
M16 x 1,5	4 – 8	10	21	17/19	6	1.610.1600.30	1.640.1600.30
M16 x 1,5	5 – 10	10	22	20/20	5	1.610.1611.30	1.640.1611.30
M20 x 1,5	5 – 9	10	23	22/22	8	1.610.2000.31	1.640.2000.31
M20 x 1,5	6 – 12	10	23	22/22	8	1.610.2000.30	1.640.2000.30
M20 x 1,5	7 – 12	10	24	24/24	10	1.610.2016.31	1.640.2016.31
M20 x 1,5	10 – 14	10	24	24/24	10	1.610.2016.30	1.640.2016.30
M25 x 1,5	10 – 16	12	26	30/30	12	1.610.2500.31	1.640.2500.31
M25 x 1,5	14 – 18	12	26	30/30	12	1.610.2500.30	1.640.2500.30
M32 x 1,5	13 – 20	12	31	40/40	15	1.610.3200.31	1.640.3200.31
M32 x 1,5	20 – 25	12	31	40/40	15	1.610.3200.30	1.640.3200.30
M40 x 1,5	20 – 26	15	37	50/50	15	1.610.4000.31	1.640.4000.31
M40 x 1,5	22 – 32	15	37	50/50	15	1.610.4000.30	1.640.4000.30
M50 x 1,5	25 – 31	15	37	57/57	24	1.610.5000.31	1.640.5000.31
M50 x 1,5	32 – 38	15	37	57/57	24	1.610.5000.30	1.640.5000.30
M63 x 1,5	29 – 35	15	38	64/68	30	1.610.6300.31	1.640.6300.31
M63 x 1,5	37 – 44	15	38	64/68	30	1.610.6300.30	1.640.6300.30



zur Montageanleitung



ATEX^{Ex}