



|                   |                          |
|-------------------|--------------------------|
| Material          | Messing vernickelt       |
| Klemmeinsatz      | Polyamid metallisiert    |
| Formdichtung      | NBR                      |
| Material O-Ring   | NBR                      |
| Schutzart         | IP 68 – 10 bar / IP 69 K |
| NEMA Type Rating  | 4 / 4X / 6               |
| Temperaturbereich | -40°C bis +100°C         |

RoHS

EMV  
EMC

// andere Dichtungsmaterialien z.B. Silikon auf Anfrage

| AG        | ∅ <sub>k</sub><br>mm | H<br>mm | SW1/SW2<br>mm | <br>Nm | GL<br>mm | Art.-Nr.<br>kurz | GL<br>mm | Art.-Nr.<br>lang |
|-----------|----------------------|---------|---------------|--------|----------|------------------|----------|------------------|
| M12 x 1,5 | 3 – 6,5              | 25      | 14/14         | 6      | 6,5      | 1.631.1200.50    | 10       | 1.631.1200.30    |
| M16 x 1,5 | 4 – 8                | 29      | 17/19         | 9      | 6        | 1.631.1609.50    | 10       | 1.631.1609.30    |
| M16 x 1,5 | 5 – 10               | 32      | 20/20         | 11     | 6        | 1.631.1600.50    | 10       | 1.631.1600.30    |
| M20 x 1,5 | 6 – 12               | 32,5    | 22/22         | 12     | 6        | 1.631.2013.50    | 10       | 1.631.2013.30    |
| M20 x 1,5 | 10 – 14              | 33      | 24/24         | 13     | 6        | 1.631.2000.50    | 10       | 1.631.2000.30    |
| M25 x 1,5 | 13 – 18              | 39      | 30/30         | 13     | 7        | 1.631.2500.50    | 12       | 1.631.2500.30    |
| M32 x 1,5 | 18 – 25              | 45      | 40/40         | 17,5   | 8        | 1.631.3200.50    | 12       | 1.631.3200.30    |
| M40 x 1,5 | 24 – 32              | 51      | 50/50         | 25     | 8        | 1.631.4000.50    | 15       | 1.631.4000.30    |
| M50 x 1,5 | 32 – 38              | 57,5    | 57/57         | 29     | 9        | 1.631.5000.50    | 15       | 1.631.5000.30    |
| M63 x 1,5 | 37 – 44              | 52      | 64/68         | 34     | 10       | 1.631.6300.50    | 15       | 1.631.6300.30    |



zum Produktvideo



zur Montageanleitung

