


Ex-Kabelverschraubungen

HSK-MZ-Ex d (metrisch, NPT)



Material	Messing vernickelt
Klemmeinsatz	Polyamid VO nach UL94
Formdichtung	FKM
Material O-Ring	FKM
Schutzart	IP 68 – 10 bar / IP 69 K
Ex-Schutzstufe	II 1D Ex ta IIIC Da / II 2G Ex db IIC Gb
Temperaturbereich	-60°C bis +105°C

RoHS

AG	∅k mm	GL mm	H mm	SW1/SW2 mm	 Nm	Art.-Nr.
M12 x 1,5	3 – 6,5	16	26	14/14	7,5	1.628.1200.50
M16 x 1,5	5 – 10	16	30,2	20/20	9	1.628.1600.50
M20 x 1,5	10 – 14	16	34	24/24	10	1.628.2000.50
M25 x 1,5	13 – 18	16	37,8	30/30	12	1.628.2500.50
M32 x 1,5	18 – 25	16	44	40/40	15	1.628.3200.50
M40 x 1,5	22 – 32	16	51,5	50/50	24	1.628.4000.50
NPT 3/8"	5 – 10	16	30	20/20	9	1.628.3800.70
NPT 1/2"	10 – 14	20	33,6	24/24	10	1.628.1200.70
NPT 3/4"	13 – 18	20,5	37,8	30/30	12	1.628.3400.70
NPT 1"	18 – 25	25	44	40/40	15	1.628.1000.70
NPT 1 1/4"	22 – 32	25	51,5	50/50	24	1.628.5400.70
NPT 1 1/2"	22 – 32	26,5	51,5	50/50	24	1.628.6400.70



zur Montageanleitung

